

Quick Reference PDU Model Guide

Basic PDU Models																				
Models	120V Pass-Through Models																			
	OEPD615HV	OEPD815HV	OEPD1415HV	OEPD1415HV-HW	OEPD1815V48	OEPD2415V62	OEPD2415V62-HW	OEPD1020HV	OEPD1020HV-HW	OEPD1420HV	OEPD2420V62	OEPD2420V62L	OEPD2420V62-HW							
	15 Amps				20 Amps															
Max Input Capacity	6 Outlets				8 Outlets				14 Outlets				18 Outlets				24 Outlets			
Outlets	6 Outlets		8 Outlets		14 Outlets				18 Outlets				24 Outlets							
Features	6 Outlets		8 Outlets		14 Outlets				18 Outlets				24 Outlets							
All-metal case	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes							
Power On/Off LED	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes							
Input Power Cord Length	15 feet	15 feet	15 feet	15 feet	15 feet	15 feet	15 feet	15 feet	15 feet	15 feet	15 feet	15 feet	15 feet							
Input Circuit Breaker Protection	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes							
Surge-protection Joule Rating	-	-	-	-	-	-	-	-	-	-	-	-	-							
Surge LED	-	-	-	-	-	-	-	-	-	-	-	-	-							
Horizontal Installation	Yes	Yes	Yes	Yes	No	No	No	Yes	Yes	Yes	No	No	No							
DU Vertical Installation	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes							
Maximum Output Rating	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps							
Front Panel Receptacles	(6) 5-15R	(2) 5-15R	(6) 5-15R	(6) 5-15/20R	(18) 5-15R	(24) 5-15R	(24) 5-15R	(2) 5-15/20R	(2) 5-15/20R	(6) 5-15/20R	(24) 5-15/20R	(24) 5-15/20R	(24) 5-15/20R							
Rear Panel Receptacles	-	(6) 5-15R	(8) 5-15R	(8) 5-15/20R	-	-	-	(8) 5-15/20R	(8) 5-15/20R	(8) 5-15/20R	-	-	-							
Input Connection	NEMA 5-15P	NEMA 5-15P	NEMA 5-15P	Hardwire	NEMA 5-15P	NEMA 5-15P	Hardwire	NEMA 5-20P	Hardwire	NEMA 5-20P	NEMA 5-20P	NEMA L5-20P	Hardwire							
62368-1 Certification	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes							

Models	208V Pass-Through Models								Surge-protected Models (120V)							
	OEPD202L620HVN	OEPD202L620HVHW	OEPD1220C13HVL	OEPD2024IECHV1	OEPD2024IECHW	OEPD302L630HVN	OEPD302L630HVHW	OEPD304L630HVN	OEPD304L630HVHW	OES1015HV	OES620V16PC6	OES1020HV	OES1020HVL			
	20 Amps				30 Amps				15 Amps		20 Amps					
Max Input Capacity	2 Outlets		12 Outlets		24 Outlets		2 Outlets		4 Outlets		10 Outlets		6 Outlets		10 Outlets	
Outlets	2 Outlets		12 Outlets		24 Outlets		2 Outlets		4 Outlets		10 Outlets		6 Outlets		10 Outlets	
Features	2 Outlets		12 Outlets		24 Outlets		2 Outlets		4 Outlets		10 Outlets		6 Outlets		10 Outlets	
All-metal case	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes			
Power On/Off LED	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes			
Input Power Cord Length	6 feet	6 feet	6 feet	6 feet	6 feet	6 feet	6 feet	6 feet	6 feet	15 feet	6 feet	15 feet	15 feet			
Input Circuit Breaker Protection	No	No	Yes	Yes	Yes	No	No	Yes	Yes	Yes	Yes	Yes	Yes			
Surge-protection Joule Rating	-	-	-	-	-	-	-	-	-	2000	2000	2000	2000			
Surge LED	-	-	-	-	-	-	-	-	-	Yes	Yes	Yes	Yes			
Horizontal Installation	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes			
DU Vertical Installation	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes			
Maximum Output Rating	20 Amps	20 Amps	16 Amps	20 Amps	20 Amps	30 Amps	30 Amps	30 Amps	30 Amps	12 Amps	16 Amps	16 Amps	16 Amps			
Front Panel Receptacles	(2) L6-20R	(2) L6-20R	(12) C13	(10) C13 / (2) C19	(10) C13 / (2) C19	(2) L6-30R	(2) L6-30R	(2) L6-20R / (2) L6-30R	(2) L6-20R / (2) L6-30R	(2) 5-15/20R	(6) 5-15/20R	(2) 5-15/20R	(2) 5-15/20R			
Rear Panel Receptacles	-	-	-	(10) C13 / (2) C19	(10) C13 / (2) C19	-	-	-	-	(8) 5-15/20R	-	(8) 5-15/20R	(8) 5-15/20R			
Input Connection	NEMA L6-20P	Hardwire	NEMA L6-20P	NEMA L6-20P	Hardwire	NEMA L6-30P	Hardwire	NEMA L6-30P	Hardwire	NEMA 5-15P	NEMA 5-20P	NEMA 5-20P	NEMA L5-20P			
62368-1 Certification	Yes	Yes	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes			

EXPAND YOUR POWER DISTRIBUTION OPTIONS WITHIN RACKS & ENCLOSURES

OEPD Series Power Distribution Units

Minuteman Power Distribution Units offer 2-24 outlets, a variety of input plug options, versatile receptacle configurations, and premium features at a lower cost.

Complete your power system installation with high quality PDU solutions from Minuteman. OEPD series PDUs feature lengthy power cords, versatile configuration options when bundled with Minuteman UPS products, and a host of premium features, all at an incredible value.

Minuteman's robust PDU line offers products ranging in capacity from 15 to 30 Amps, in both vertical and horizontal orientations. In addition, select models also feature surge suppression capabilities. OEPD power cords are strain-relieved with molded plugs or come with IEC inputs that use locking brackets for safety, and use heavy-gauged cables.

All models have an external ground stud.

Designed for:

- Data Center Server Racks
- Telecommunications systems with multiple components
- Security systems with multiple components
- IDF/MDF closets with multiple network devices



Connection through **POWER**

minutemanups.com | 800.238.7272

Quick Reference PDU Model Guide

Managed PDU Models																
Models	120V Models															
	RPM1521E	RPM1581HVN	RPM1581EV6	RPM158N1CD	RPM1516N1CD	RPM1524N1CD	RPM208N1CD	RPM2016N1CD	RPM20161VN	RPM2024N1CD	RPM308N1CD-HW	RPM3016N1CD-HW	RPM30241EV6	RPM3024N1CD-HW		
	15 Amps						20 Amps				30 Amps					
Max Input Capacity	2-Outlet		8 Outlets			16 Outlets		24 Outlets		8 Outlets		16 Outlets		24 Outlets		
Outlets	2-Outlet		8 Outlets			16 Outlets		24 Outlets		8 Outlets		16 Outlets		24 Outlets		
Features	2-Outlet		8 Outlets			16 Outlets		24 Outlets		8 Outlets		16 Outlets		24 Outlets		
All-metal case	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes		
Input Power Cord Length	6 feet	10 feet	10 feet	10 feet	10 feet	10 feet	10 feet	10 feet	10 feet	10 feet	10 feet	10 feet	10 feet	10 feet		
Input Circuit Breaker Protection	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes		
Horizontal Installation	Yes	Yes	Yes	Yes	No	No	Yes	No	No	No	Yes	No	No	No		
DU Vertical Installation	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes		
Maximum Output Rating	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	16 Amps	16 Amps	16 Amps	16 Amps	24 Amps	24 Amps	24 Amps	24 Amps		
Front Panel Receptacles	-	(8) 5-15R	-	-	(16) 5-15R	(24) 5-15R	-	(16) 5-15/20R	(16) 5-15R	(24) 5-15/20R	-	(16) 5-15/20R	(24) 5-15R	(24) 5-15/20R		
Rear Panel Receptacles	(2) 5-15R	-	(8) 5-15R	(8) 5-15R	-	-	(8) 5-15/20R	-	-	-	(8) 5-15/20R	-	-	-		
Standard Input Connection	NEMA 5-15P	NEMA 5-15P	NEMA 5-15P	IEC320 C20	IEC320 C20	IEC320 C20	IEC320 C20	IEC320 C20	NEMA 5-20P	IEC320 C20	Hardwire	Hardwire	NEMA L5-30P	Hardwire		
NEMA Input Option	-	-	-	"-15P"	"-15P"	"-15P"	"-20P" / "-L20P"	"-20P" / "-L20P"	-	"-20P" / "-L20P"	"-L30P"	"-L30P"	-	"-L30P"		
IEC Input Option	-	-	-	"-IEC"	"-IEC"	"-IEC"	"-IEC"	"-IEC"	"-IEC"	"-IEC"	-	-	-	-		
Hardwire Input Option	-	-	-	"-HW"	"-HW"	"-HW"	"-HW"	"-HW"	"-HW"	"-HW"	-	-	-	-		
IPv6 Support	No	No	Yes	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes	Yes	Yes		
SNMPv3 Support	Yes	No	Yes	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes	Yes	Yes		
Individual & Grouped Outlet Control	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes		
Configurable Auto-Alarm Response	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes		
Auto-ping/Heartbeat Monitoring	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes		
TLS/SSL Secure E-mail Notices	Yes	No	Yes	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes	Yes	Yes		
SNMP or Web Browser Control	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes		
Scheduled Shutdown/Restart	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes		
62368-1 Certification	No	Yes	No	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes	No	Yes		

208V Models																	
Models	RPM2042LCD-L20P	RPM2082HVI	RPM20812LCD-L20P	RPM20162VI	RPM201612LCD-L20P	RPM20242LCD-L20P	RPM30812LCD-HW	RPM301612LCD-HW	RPM30242EV6	RPM302412LCD-HW							
	20 Amps						30 Amps										
	Max Input Capacity	4 Outlets		8 Outlets			16 Outlets		24 Outlets		8 Outlets			16 Outlets		24 Outlets	
Outlets	4 Outlets		8 Outlets			16 Outlets		24 Outlets		8 Outlets			16 Outlets		24 Outlets		
Features	4 Outlets		8 Outlets			16 Outlets		24 Outlets		8 Outlets			16 Outlets		24 Outlets		
All-metal case	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes			
Input Power Cord Length	10 feet	10 feet	10 feet	10 feet	10 feet	10 feet	10 feet	10 feet	10 feet	10 feet	10 feet	10 feet	10 feet	10 feet			
Input Circuit Breaker Protection	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes			
Horizontal Installation	Yes	Yes	Yes	No	No	No	Yes	No	No	No	Yes	No	No	No			
DU Vertical Installation	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes			
Maximum Output Rating	20 Amps	20 Amps	20 Amps	20 Amps	20 Amps	20 Amps	24 Amps	24 Amps	24 Amps	24 Amps	24 Amps	24 Amps	24 Amps	24 Amps			
Front Panel Receptacles	-	-	-	(14) C13 / (2) C19	(14) C13 / (2) C19	(21) C13 / (3) C19	-	(14) C13 / (2) C19	(21) C13 / (3) C19	(21) C13 / (3) C19	-	-	-	-			
Rear Panel Receptacles	(4) C13	(8) C13	(8) C13	-	-	-	(8) C13	-	-	-	-	-	-	-			
Standard Input Connection	NEMA L6-20P	NEMA 6-20P	NEMA L6-20P	NEMA 6-20P	NEMA L6-20P	NEMA L6-20P	Hardwire	Hardwire	NEMA L6-30P	Hardwire	-	-	-	-			
NEMA Input Option	-	-	-	-	-	-	"-L30P"	"-L30P"	-	"-L30P"	-	-	-	-			
IEC Input Option	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
Hardwire Input Option	"-HW"	-	"-HW"	-	"-HW"	"-HW"	-	-	-	-	-	-	-	-			
IPv6 Support	Yes	No	Yes	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes			
SNMPv3 Support	Yes	No	Yes	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes			
Individual & Grouped Outlet Control	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes			
Configurable Auto-Alarm Response	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes			
Auto-ping/Heartbeat Monitoring	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes			
TLS/SSL Secure E-mail Notices	Yes	No	Yes	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes			
SNMP or Web Browser Control	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes			
Scheduled Shutdown/Restart	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes			
62368-1 Certification	Yes	Yes	Yes	No	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes	No	Yes			



Scan here for our full Product Catalog Specifications

minutemanups.com | 800.238.7272

Utilizing Minuteman's remote power manager products allows technicians and administrators to:

- Save Time:** Reboot remote devices in seconds, not minutes or hours
- Cut Costs:** Eliminate service calls to remote locations by managing devices from your computer or smartphone
- Increase Productivity:** Eliminate help desk calls & lost time when a device locks up; RPM notifies & provides automatic reboot capabilities

Minuteman RPMs can control and configure all aspects of the device, including:

- LAN Connection:** The RPM is an IP-based PDU that connects to your network via CAT5 cable
- Control Individual Outlets:** Power on/off, reboot, and monitor up to 16 individual devices from a single IP address
- Scheduled Management Actions:** save power with automatic shutdown and startup of devices over weekends or holidays
- Notifications via SNMP, SMS Text, or Email:** To keep you informed of events such as a server shutdown, the RPM can submit its notifications via SMS text message, or email to up to three addresses