

Feature Comparison Chart of MM OEPD Series vs. APC AP Series*

FEATURES	APC AP Series		Minuteman OEPD Series				
	AP9562	AP9567	OEPD615HV	OEPD815HV	OEPD1415HV / -HW	OEPD1815V48	OEPD2415V62 / -HW
Input							
On/Off Switch	No	No	No	No	No	No	No
Power On/Off LED	No	No	Yes	Yes	Yes	Yes	Yes
Input Power Cord Length	12-feet	12-feet	15-feet	15-feet	15-feet	15-feet	15-feet
Input Connection	NEMA 5-15P	NEMA 5-15P	NEMA 5-15P	NEMA 5-15P	NEMA 5-15P / (-HW) Hardwire	NEMA 5-15P	NEMA 5-15P / (-HW) Hardwire
Input Circuit Breaker Protection	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Input Voltage Range	100-120V	100-120V	120V	120V	120V	120V	120V
Max Input Current	15 Amps	15 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps
Output							
Maximum Output Rating (A)	N/A	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps
Output Voltage Range	120V	100-120V	120V	120V	120V	120V	120V
Max Capacity (W)	1400 Watts	1400 Watts	1440 Watts	1440 Watts	1440 Watts	1440 Watts	1440 Watts
Number of Output Circuits	N/A	N/A	One	One	One	One	One
Front Panel Receptacles	N/A	N/A	N/A	(2) NEMA 5-15R	(6) NEMA 5-15R	(18) NEMA 5-15R	(24) NEMA 5-15R
Rear Panel Receptacles	(10) NEMA 5-15R	(14) NEMA 5-15R	(6) NEMA 5-15R	(6) NEMA 5-15R	(8) NEMA 5-15R	N/A	N/A
Surge Protection							
Surge-protection Joule Rating	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Earth-ground Lug	N/A	N/A	Yes	Yes	Yes	Yes	Yes
Physical							
All-metal case	N/A	N/A	Yes	Yes	Yes	Yes	Yes
Horizontal Installation	Yes	Yes	Yes	Yes	Yes	No	No
OU Vertical Installation	No	Yes	Yes	Yes	Yes	Yes	Yes
Customization Options	1U	1U, 0U	1U, 0U	1U, 0U	1U, 0U	0U, Wallmount	0U, Wallmount
Warranty & Certifications							
62368-1 Certification	N/A	N/A	Yes	Yes	Yes	Yes	Yes
Other Certifications	cUL, METI Denan, UL	cUL, METI Denan, UL	cUL, UL1077, CE	cUL, UL1077, CE	cUL, UL1077, CE	cUL, UL1077, CE	cUL, UL1077, CE
Warranty	2 Years	2 Years	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime

All names and trademarks are the property of the respective companies.

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

((Brand) Advantage in **BOLD**)

(MM Advantage in **BOLD**)

Feature Comparison Chart of MM OEPD Series vs. APC AP Series*

FEATURES	APC AP Series				Minuteman OEPD Series	
	AP9563	AP7530	AP9551	AP9564	OEPD1020HV /-HW	OEPD2420V62 /-L /-HW
Input						
On/Off Switch	No	No	No	No	No	No
Power On/Off LED	No	No	No	No	Yes	Yes
Input Power Cord Length	12-feet	10-feet	12-feet	12-feet	15-feet	15-feet
Input Connection	NEMA 5-20P	NEMA L5-20P	NEMA L5-20P	NEMA L5-20P	NEMA 5-20P	NEMA 5-20P / (-L) L5-20P / (-HW) Hardwire
Input Circuit Breaker Protection	Yes	No	Yes	Yes	Yes	Yes
Input Voltage Range	100-120V	120V	100-120V	100-120V	120V	120V
Max Input Current	20 Amps	20 Amps	20 Amps	20 Amps	20 Amps	20 Amps
Output						
Maximum Output Rating (A)	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps
Output Voltage Range	100-120V	120V	100-120V	100-120V	120V	120V
Max Capacity (W)	1900 Watts	1920 Watts	1900 Watts	1900 Watts	1920 Watts	1920 Watts
Number of Output Circuits	N/A	N/A	N/A	N/A	One	One
Front Panel Receptacles	N/A	(24) NEMA 5-20R	N/A	N/A	(2) NEMA 5-15/20R	(24) NEMA 5-15/20R
Rear Panel Receptacles	(10) NEMA 5-20R	N/A	(14) NEMA 5-15R	(10) NEMA 5-20R	(8) NEMA 5-15/20R	N/A
Surge Protection						
Surge-protection Joule Rating	N/A	N/A	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A	N/A	N/A
Earth-ground Lug	No	No	No	No	Yes	Yes
Physical						
All-metal case	Yes	N/A	N/A	N/A	Yes	Yes
Horizontal Installation	Yes	Yes	No	Yes	Yes	No
0U Vertical Installation	Yes	Yes	Yes	Yes	Yes	Yes
Customization Options	1U, 0U	1U, 0U	0U	1U, 0U	1U, 0U	0U, Wallmount
Warranty & Certifications						
62368-1 Certification	No	No	No	No	Yes	Yes
Other Certifications	cUL, UL	UL 60950-1, cUL, UL	cULus, CSA	cULus	cUL, UL 1077, CE	cUL, UL 1077, CE
Warranty	2 Years	2 Years	2 Years	2 Years	Lifetime	Lifetime

All names and trademarks are the property of the respective companies.

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

((Brand) Advantage in **BOLD**)

(MM Advantage in **BOLD**)

Feature Comparison Chart of MM OEPD Series vs. APC AP Series*

FEATURES	APC AP Series			Minuteman OEPD Series	
	AP9566	AP7540	AP7552	OEPD202L620HVN / -HW	OEPD2024IECHVI /-HW
Input					
On/Off Switch	No	No	No	No	No
Power On/Off LED	No	No	No	No	No
Input Power Cord Length	12-feet	10-feet	10-feet	6-feet	6 feet
Input Connection	NEMA L6-20P	NEMA L6-20P	IEC C20	NEMA L6-20P / (-HW) Hardwire	NEMA L6-20P / (-HW) Hardwire
Input Circuit Breaker Protection	No	No	No	No	Yes
Input Voltage Range	200-240V	200-240V	230V	200-240V	200-240V
Max Input Current	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps
Output					
Maximum Output Rating (A)	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps
Output Voltage Range	208V	208V	230V	208V-240V	208V-240V
Max Capacity (W)	3300 Watts	3300 Watts	3700 Watts	3840 Watts	3840 Watts
Number of Output Circuits	N/A	N/A	N/A	One	One
Front Panel Receptacles	N/A	(20) IEC320 C13 / (4) IEC320 C19	(20) IEC320 C13 / (4) IEC320 C19	(2) NEMA L6-20R	(10) IEC320 C13 / (2) IEC320 C19
Rear Panel Receptacles	(12) IEC320 C13	N/A	N/A	No	(10) IEC320 C13 / (2) IEC320 C19
Surge Protection					
Surge-protection Joule Rating	N/A	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A	N/A
Earth-ground Lug	No	No	No	No	No
Physical					
All-metal case	N/A	N/A	N/A	Yes	Yes
Horizontal Installation	Yes	No	No	Yes	Yes
0U Vertical Installation	Yes	Yes	Yes	Yes	Yes
Customization Options	1U, 0U	0U	0U	1U, 0U	1U, 0U
Warranty & Certifications					
62368-1 Certification	No	No	No	Yes	Yes
Other Certifications	cUL, UL, UL-60950	cUL, UL, UL-60950	UL-EC, CE, RCM, EAC, KC, UKCA	cETLus, CE	cETLus, CE
Warranty	2 Years	2 Years	2 Years	Lifetime	Lifetime

All names and trademarks are the property of the respective companies.

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

((Brand) Advantage in **BOLD**)

(MM Advantage in **BOLD**)

Feature Comparison Chart of MM OEPD Series vs. APC AP Series*

FEATURES	APC AP Series				Minuteman OEPD Series	
	AP7541	AP9571A	AP9570	AP6002A	OEPD302L630HVN / -HW	OEPD304L630HVN / -HW
Input						
On/Off Switch	Yes	Yes	Yes	Yes	No	No
Power On/Off LED	No	No	No	No	No	No
Input Power Cord Length	10-feet	12-feet	10-feet	10-feet	6 feet	6 feet
Input Connection	NEMA L6-30P	NEMA L6-30P	NEAM L6-30P	NEMA L6-30P	NEMA L6-30P / (-HW) Hardwire	NEMA L6-30P / (-HW) Hardwire
Input Circuit Breaker Protection	No	(2) 20 Amp	(2) 20 Amp	(2) 20 Amp	No	No
Input Voltage Range	200V-240V	200V-240V	200V-240V	200V-240V	200V-240V	200V-240V
Max Input Current	24 Amps	24 Amps	24 Amps	24 Amps	24 Amps	24 Amps
Output						
Maximum Output Rating (A)	24 Amps	24 Amps	24 Amps	24 Amps	24 Amps	24 Amps
Output Voltage Range	200-240V	200-240V	208V	200-240V	200-240V	200-240V
Max Capacity (W)	4992 VA	4992 VA	5000 Watts	5000 Watts	5760 Watts	5760 Watts
Number of Output Circuits	N/A	N/A	N/A	N/A	N/A	(1) 30 Amp / (2) 20 Amp
Front Panel Receptacles	(20) IEC320 C13 / (4) IEC320 C19	N/A	N/A	N/A	(2) L6-30R	(2) NEMA L6-20R / (2) NEMA L6-30R
Rear Panel Receptacles	N/A	(10) IEC320 C13	(4) IEC320 C19	(14) IEC320 C13 / (2) IEC320 C19	N/A	N/A
Surge Protection						
Surge-protection Joule Rating	N/A	N/A	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A	N/A	N/A
Earth-ground Lug	No	No	No	No	N/A	N/A
Physical						
All-metal case	N/A	N/A	N/A	N/A	Yes	Yes
Horizontal Installation	Yes	Yes	Yes	No	Yes	Yes
0U Vertical Installation	Yes	Yes	Yes	Yes	Yes	Yes
Customization Options	1U, 0U	1U, 0U	1U, 0U	0U	1U, 0U	1U, 0U
Warranty & Certifications						
62368-1 Certification	No	No	No	No	Yes	Yes
Other Certifications	cUL, UL, METI, PSE	cUL, UL, PSE	cUL, UL, METI, PSE	cUL, UL, PSE	cETLus/CE	cETLus/CE
Warranty	2 Years	2 Years	2 Years	2 Years	Lifetime	Lifetime

All names and trademarks are the property of the respective companies.

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

((Brand) Advantage in **BOLD**)

(MM Advantage in **BOLD**)

Feature Comparison Chart of MM OEPD Series vs. Cyber Power PDU-B Series*

FEATURES	Cyber Power PDU-B Series							Minuteman OEPD Series				
	PDU15B8R	PDU15B10R	PDU15B12R	PDU15B2F8R	PDU15B2F10R	PDU15B2F12R	PDU15B6F12R	OEPD615HV	OEPD815HV	OEPD1415HV /-HW	OEPD1815V48	OEPD2415V62 /-HW
Input												
On/Off Switch	No	No	No	No	No	No	No	No	No	No	No	No
Power On/Off LED	No	No	No	No	No	No	No	Yes	Yes	Yes	Yes	Yes
Input Power Cord Length	15 feet	15 feet	15 feet	15 feet	15 feet	15 feet	15 feet	15-feet	15-feet	15-feet	15-feet	15-feet
Input Connection	NEMA 5-15P	NEMA 5-15P	NEMA 5-15P	NEMA 5-15P	NEMA 5-15P	NEMA 5-15P	NEMA 5-15P	NEMA 5-15P	NEMA 5-15P	NEMA 5-15P / (-HW) Hardwire	NEMA 5-15P	NEMA 5-15P / (-HW) Hardwire
Input Circuit Breaker Protection	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Input Voltage Range	100-125V	100-125V	100-125V	100-125V	100-125V	100-125V	100-125V	120V	120V	120V	120V	120V
Max Input Current	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps
Output												
Maximum Output Rating (A)	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps
Output Voltage Range	100-125V	100-125V	100-125V	100-125V	100-125V	100-125V	100-125V	120V	120V	120V	120V	120V
Max Capacity (W)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	1440 Watts	1440 Watts	1440 Watts	1440 Watts	1440 Watts
Number of Output Circuits	N/A	N/A	N/A	N/A	N/A	N/A	N/A	One	One	One	One	One
Front Panel Receptacles	N/A	N/A	N/A	(2) NEMA 5-15R	(2) NEMA 5-15R	(2) NEMA 5-15R	(6) NEMA 5-15R	N/A	(2) NEMA 5-15R	(6) NEMA 5-15R	(18) NEMA 5-15R	(24) NEMA 5-15R
Rear Panel Receptacles	(8) NEMA 5-15R	(10) NEMA 5-15R	(12) NEMA 5-15R	(8) NEMA 5-15R	(10) NEMA 5-15R	(12) NEMA 5-15R	(12) NEMA 5-15R	(6) NEMA 5-15R	(6) NEMA 5-15R	(8) NEMA 5-15R	N/A	N/A
Surge Protection												
Surge-protection Joule Rating	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Earth-ground Lug	N/A	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Physical												
All-metal case	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Horizontal Installation	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No	No
0U Vertical Installation	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Customization Options	1U, 0U, Wallmount, Under-counter	1U, 0U, Wallmount, Under-counter	1U, 0U, Wallmount, Under-counter	1U, 0U, Wallmount, Under-counter	1U, 0U, Wallmount, Under-counter	1U, 0U, Wallmount, Under-counter	1U, 0U, Wallmount, Under-counter	1U, 0U	1U, 0U	1U, 0U	0U, Wallmount	0U, Wallmount
Warranty & Certifications												
62368-1 Certification	No	No	No	No	No	No	No	Yes	Yes	Yes	Yes	Yes
Other Certifications	RoHS, UL1363, CSA	RoHS, UL1363, CSA	RoHS, UL1363, CSA	RoHS, UL1363, CSA	RoHS, UL1363, CSA	RoHS, UL1363, CSA	RoHS, UL1363, CSA	cUL, UL1077, CE	cUL, UL1077, CE	cUL, UL1077, CE	cUL, UL1077, CE	cUL, UL1077, CE
Warranty	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

All names and trademarks are the property of the respective companies.

((Brand) Advantage in **BOLD**)

(MM Advantage in **BOLD**)

Feature Comparison Chart of MM OEPD Series vs. Cyber Power PDU-B Series*

FEATURES	Cyber Power PDU-B Series								Minuteman OEPD Series	
	PDU20B10R	PDU20B2F12R	PDU20BVT14F	PDU20BVT16F	PDU20BVT6F12R	PDU20BVT20F	PDU20BVT28F	PDU20BV32F / -T32F	OEPD1020HV /-HW	OEPD2420V62 /-L /-HW
Input										
On/Off Switch	No	No	No	No	No	No	No	No	No	No
Power On/Off LED	No	No	No	No	No	No	No	No	Yes	Yes
Input Power Cord Length	15-feet	15- *feet	10-feet	10-feet	15-feet	10-feet	10-feet	10 feet	15-feet	15-feet
Input Connection	NEMA 5-20P	NEMA 5-20P	NEMA L5-20P	NEMA L5-20P	NEMA L5-20P	NEMA L5-20P	NEMA L5-20P	NEMA 5-20P / NEMA L5-20P	NEMA 5-20P	NEMA 5-20P / (-L) L5-20P / (-HW) Hardwire
Input Circuit Breaker Protection	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Input Voltage Range	100-125V	100-125V	100-125V	100-125V	100-125V	100-125V	100-125V	100-125V	120V	120V
Max Input Current	20 Amps	20 Amps	20 Amps	20 Amps	20 Amps	21 Amps	20 Amps	20 Amps	20 Amps	20 Amps
Output										
Maximum Output Rating (A)	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps
Output Voltage Range	100-125V	100-125V	100-125V	100-125V	100-125V	100-125V	100-125V	100-125V	120V	120V
Max Capacity (W)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	1920 Watts	1920 Watts
Number of Output Circuits	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	One	One
Front Panel Receptacles	N/A	(2) NEMA 5-20R	(14) NEMA 5-20R	(16) NEMA 5-20R	(6) NEMA 5-20R	(20) NEMA 5-20R	(28) NEMA 5-20R	(32) NEMA 5-20R	(2) NEMA 5-15/20R	(24) NEMA 5-15/20R
Rear Panel Receptacles	(10) NEMA 5-20R	(12) NEMA 5-20R	N/A	N/A	(12) NEMA 5-20R	N/A	N/A	N/A	(8) NEMA 5-15/20R	N/A
Surge Protection										
Surge-protection Joule Rating	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Earth-ground Lug	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Physical										
All-metal case	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Horizontal Installation	Yes	Yes	No	No	No	No	No	No	Yes	No
OU Vertical Installation	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Customization Options	1U,0U, Wallmount, Under-counter	1U, 0U, Wallmount, Under-counter	0U, Wallmount, Under- counter	0U, Wallmount, Under- counter	0U, Wallmount, Under- counter	0U, Wallmount, Under- counter	0U, Wallmount, Under- counter	0U, Wallmount, Under- counter	1U, 0U	0U, Wallmount
Warranty & Certifications										
62368-1 Certification	No	No	No	No	No	No	No	No	Yes	Yes
Other Certifications	RoHS, UL 1363	RoHS, UL 1363, CSA	RoHS, UL 1363, CSA	RoHS, UL 1363, CSA	RoHS, UL 1363, CSA	RoHS, UL 1363, CSA	RoHS, UL 1363, CSA	RoHS, UL 1363, CSA	cUL, UL 1077, CE	cUL, UL 1077, CE
Warranty	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

All names and trademarks are the property of the respective companies.

((Brand) Advantage in **BOLD**)
(MM Advantage in **BOLD**)

Feature Comparison Chart of MM OEPD Series vs. Cyber Power PDU Series*

FEATURES	Cyber Power PDU Series												Minuteman OEPD Series	
	PDU208HVT12R	PDU208HVT8R	PDU208HVHT20F	PDU208HVHT24F	PDU208HVIEC8R	PDU208HVIEC12R	PDU208HVIEC12RA	PDU208HVHIEC16F	PDU208HVHIEC20F	PDU208HVHIEC24F	PDU208HVHIEC32F	PDU208HVHIEC38F	OEPD202L620HVN / -HW	OEPD2024IECHV1 / -HW
Input														
On/Off Switch	No	No	No	No	No	No	No	No	No	No	No	No	No	No
Power On/Off LED	No	No	No	No	No	No	No	No	No	No	No	No	No	No
Input Power Cord Length	10-feet	10-feet	10-feet	10-feet	10-feet	10-feet	10-feet	10-feet	10-feet	10-feet	10-feet	10-feet	6-feet	6 feet
Input Connection	NEMA L6-20P	NEMA L6-20P	NEMA L6-20P	NEMA L6-20P	IEC-C20	IEC-C20	IEC-C20	IEC-C20	IEC-C20	IEC-C20	IEC-C20	IEC-C20	NEMA L6-20P / (-HW) Hardwire	NEMA L6-20P / (-HW) Hardwire
Input Circuit Breaker Protection	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No	Yes
Input Voltage Range	200-230V	200-230V	200-230V	200-230V	200-230V	200-230V	200-230V	200-230V	200-230V	200-230V	200-230V	200-230V	200-240V	200-240V
Max Input Current	20 Amps	20 Amps	20 Amps	20 Amps	20 Amps	20 Amps	20 Amps	20 Amps	20 Amps	20 Amps	20 Amps	20 Amps	16 Amps	16 Amps
Output														
Maximum Output Rating (A)	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps
Output Voltage Range	200-230V	200-230V	200-230V	200-230V	200-230V	200-230V	200-230V	200-230V	200-230V	200-230V	200-230V	200-230V	208V-240V	208V-240V
Max Capacity (W)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	3840 Watts	3840 Watts
Number of Output Circuits	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	One	One
Front Panel Receptacles	N/A	N/A	N/A	(4) IEC320 C19 / (20) IEC320 C13	N/A	N/A	N/A	(16) IEC320 C13	(4) IEC320 C19 / (16) IEC320 C13	(4) IEC320 C19 / (20) IEC320 C13	(8) IEC320 C19 / (24) IEC320 C13	(8) IEC320 C19 / (30) IEC320 C13	(2) NEMA L6-20R	(10) IEC320 C13 / (2) IEC320 C19
Rear Panel Receptacles	(12) IEC320 C13	(2) IEC320 C19 / (6) IEC320 C13	(4) IEC320 C19 / (16) IEC320 C13	N/A	(8) IEC320 C13	(12) IEC320 C13	(2) IEC320 C19 / (10) IEC320 C13	N/A	N/A	N/A	N/A	N/A	No	(10) IEC320 C13 / (2) IEC320 C19
Surge Protection														
Surge-protection Joule Rating	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Earth-ground Lug	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No	No
Physical														
All-metal case	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Horizontal Installation	Yes	Yes	No	No	Yes	Yes	Yes	No	No	No	No	No	Yes	Yes
0U Vertical Installation	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Customization Options	1U, 0U, Wallmount, Under-counter	1U, 0U, Wallmount, Under-counter	0U, Wallmount, Under-counter	0U, Wallmount, Under-counter	1U, 0U, Wallmount, Under-counter	1U, 0U, Wallmount, Under-counter	1U, 0U, Wallmount, Under-counter	0U, Wallmount, Under-counter	0U, Wallmount, Under-counter	0U, Wallmount, Under-counter	0U, Wallmount, Under-counter	0U, Wallmount, Under-counter	1U, 0U	1U, 0U
Warranty & Certifications														
62368-1 Certification	No	No	No	No	No	No	No	No	No	No	No	No	Yes	Yes
Other Certifications	RoHS, UL60950-1	RoHS, UL60950-1	RoHS, UL60950-1	RoHS, UL60950-1	RoHS, UL60950-1	RoHS, UL60950-1	RoHS, UL60950-1	RoHS, UL60950-2, CSA	RoHS, UL60950-2, CSA	RoHS, UL60950-2, CSA	RoHS, UL60950-2, CSA	RoHS, UL60950-2, CSA	cETLus, CE	cETLus, CE
Warranty	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

All names and trademarks are the property of the respective companies.

((Brand) Advantage in **BOLD**)

(MM Advantage in **BOLD**)

Feature Comparison Chart of MM OEPD Series vs. Cyber Power PDU Series*

FEATURES	Cyber Power PDU Series			Minuteman OEPD Series	
	PDU30BHVT8R	PDU30BHVT12R	PDU30BVHVT32F	OEPD302L630HVN /-HW	OEPD304L630HVN /-HW
Input					
On/Off Switch	No	No	No	No	No
Power On/Off LED	Yes	Yes	No	No	No
Input Power Cord Length	10 feet	10 feet	10 feet	6 feet	6 feet
Input Connection	NEMA L6-30P	NEMA L6-30P	NEMA L6-30P	NEMA L6-30P / (-HW) Hardwire	NEMA L6-30P / (-HW) Hardwire
Input Circuit Breaker Protection	Yes, (2) 16 Amp	Yes, (2) 16 Amp	Yes, (2) 16 Amp	No	No
Input Voltage Range	208-230V	200-230V	200-230V	200V-240V	200V-240V
Max Input Current	24 Amps	24 Amps	24 Amps	24 Amps	24 Amps
Output					
Maximum Output Rating (A)	24 Amps	24 Amps	24 Amps	24 Amps	24 Amps
Output Voltage Range	200-230V	200-230V	200-230V	200V-240V	200V-240V
Max Capacity (W)	N/A	N/A	N/A	5760 Watts	5760 Watts
Number of Output Circuits	N/A	N/A	N/A	N/A	(1) 30 Amp / (2) 20 Amp
Front Panel Receptacles	N/A	N/A	(8) IEC320 C19 / (24) IEC320 C13	(2) NEMA L6-30R	(2) NEMA L6-20R / (2) NEMA L6-30R
Rear Panel Receptacles	(6) IEC320 C13 / (2) IEC320 C19	(12) IEC320 C13	N/A	N/A	N/A
Surge Protection					
Surge-protection Joule Rating	N/A	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A	N/A
Earth-ground Lug	Yes	Yes	Yes	N/A	N/A
Physical					
All-metal case	Yes	Yes	Yes	Yes	Yes
Horizontal Installation	Yes	Yes	No	Yes	Yes
0U Vertical Installation	Yes	Yes	Yes	Yes	Yes
Customization Options	1U, 0U, Wallmount, Under-counter	1U, 0U, Wallmount, Under-counter	0U, Wallmount	1U, 0U	1U, 0U
Warranty & Certifications					
62368-1 Certification	No	No	No	Yes	Yes
Other Certifications	RoHS, UL60950_1, CSA	RoHS, UL60950_1, CSA	RoHS, UL60950_1, CSA	cETLus/CE	cETLus/CE
Warranty	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime

All names and trademarks are the property of the respective companies.

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

((Brand) Advantage in **BOLD**)

(MM Advantage in **BOLD**)

Feature Comparison Chart of MM OEPD Series vs. Tripp Lite PDU*

FEATURES	Tripp Lite Basic PDU Series					Minuteman OEPD Series				
	PDU1215	PDU121506	PDU1415	PDUV15	PDUV15-48	OEPD615HV	OEPD815HV	OEPD1415HV /-HW	OEPD1815V48	OEPD2415V62 /-HW
Input										
On/Off Switch	No	No	No	No	Yes	No	No	No	No	No
Power On/Off LED	No	No	No	No	Yes	Yes	Yes	Yes	Yes	Yes
Input Power Cord Length	15-feet	6-feet	15-feet	15-feet	15-feet	15-feet	15-feet	15-feet	15-feet	15-feet
Input Connection	NEMA 5-15P	NEMA 5-15P	NEMA 5-15P	NEMA 5-15P	NEMA 5-15p	NEMA 5-15P	NEMA 5-15P	NEMA 5-15P / (-HW) Hardwire	NEMA 5-15P	NEMA 5-15P / (-HW) Hardwire
Input Circuit Breaker Protection	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Input Voltage Range	120V	120V	120V	120V	120V	120V	120V	120V	120V	120V
Max Input Current	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps
Output										
Maximum Output Rating (A)	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps
Output Voltage Range	120V	120V	120V	120V	120V	120V	120V	120V	120V	120V
Max Capacity (W)	1800 Watts	1800 Watts	1800 Watts	1440 Watts	1,440 Watts	1440 Watts	1440 Watts	1440 Watts	1440 Watts	1440 Watts
Number of Output Circuits	N/A	N/A	N/A	N/A	N/A	One	One	One	One	One
Front Panel Receptacles	(1) NEMA 5-15R	(1) NEMA 5-15R	(14) NEMA 5-15R	(15) NEMA 5-15R	(16) NEMA 5-15R	N/A	(2) NEMA 5-15R	(6) NEMA 5-15R	(18) NEMA 5-15R	(24) NEMA 5-15R
Rear Panel Receptacles	(12) NEMA 5-15R	(12) NEMA 5-15R	N/A	N/A	N/A	(6) NEMA 5-15R	(6) NEMA 5-15R	(8) NEMA 5-15R	N/A	N/A
Surge Protection										
Surge-protection Joule Rating	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Earth-ground Lug	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes	Yes	Yes
Physical										
All-metal case	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Horizontal Installation	Yes	Yes	No	No	No	Yes	Yes	Yes	No	No
0U Vertical Installation	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Customization Options	1U, 0U, Wallmount, Undercounter	1U, 0U, Wallmount, Undercounter	0U, Wallmount	0U, Wallmount, Undercounter	0U, Wallmount, Undercounter	1U, 0U	1U, 0U	1U, 0U	0U, Wallmount	0U, Wallmount
Warranty & Certifications										
62368-1 Certification	No	No	No	No	No	Yes	Yes	Yes	Yes	Yes
Other Certifications	RETIE, CSA, NOM, UL1363	RETIE, CSA, NOM, UL1363	CSA, NOM, UL60950-1, RoHS	CSA, NOM, UL60950-1, RoHS	CSA, UL 60950-1, RoHS	cUL, UL1077, CE	cUL, UL1077, CE	cUL, UL1077, CE	cUL, UL1077, CE	cUL, UL1077, CE
Warranty	5 Years	5 Years	5 Years	5 Years	2 Years	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

All names and trademarks are the property of the respective companies.

((Brand) Advantage in **BOLD**)
(MM Advantage in **BOLD**)

Feature Comparison Chart of MM OEPD Series vs. Tripp Lite PDU Series*

FEATURES	Tripp Lite PDU							Minuteman OEPD Series	
	PDU1220 /-T /-6	PDU1226	PDUV20	PDU1420T	PDUV20-60	PDUV20-72	PDU40TDUAL	OEPD1020HV /-HW	OEPD2420V62 /-L /-HW
Input									
On/Off Switch	No	No	No	No	Yes	Yes	No	No	No
Power On/Off LED	No	No	No	No	Yes	Yes	No	Yes	Yes
Input Power Cord Length	15-ft / (-T) 15-ft / (-6) 6-ft	6-feet	15-feet	15-feet	15-feet	15-feet	Two 10-feet	15-feet	15-feet
Input Connection	NEMA 5-20P/ NEMA L5-20P	NEMA 5-20P	NEMA 5-20P/ NEMA L5-20P	NEMA L5-20P	NEMA L5-20P (w/5-20P Adaptor)	NEMA L5-20P (w/5-20P Adaptor)	NEMA L5-20P (w/5-20P Adaptor)	NEMA 5-20P	NEMA 5-20P / (-L) L5-20P / (-HW) Hardwire
Input Circuit Breaker Protection	Yes	Yes	Yes	Yes	Yes	Yes	Yes, (2) 16 Amp	Yes	Yes
Input Voltage Range	120V	120V	120V	120V	120V	100-127V	120V	120V	120V
Max Input Current	20 Amp	20 Amp	16 Amp	20 Amps	16 Amps	16 Amps	16 Amp	20 Amps	20 Amps
Output									
Maximum Output Rating (A)	16 Amps	16 Amp	16 Amp	16 Amps	16 Amps	16 Amps	16 Amp	16 Amps	16 Amps
Output Voltage Range	120V	120V	120V	120V	120V	100-127V	120V	120V	120V
Max Capacity (W)	2,400 Watts	2,400 Watts	1,920 Watts	2,400 Watts	1,920 Watts	1,600-2030 Watts	3,800 Watts (1,900 Watts ea. Circuit)	1920 Watts	1920 Watts
Number of Output Circuits	N/A	N/A	N/A	N/A	N/A	N/A	N/A	One	One
Front Panel Receptacles	(1) NEMA 5-15/20R	(1) NEMA 5-15/20R	(14) NEMA 5-15/20R	(14) NEMA 5-15/20R	(28) NEMA 5-15/20R	(36) NEMA 5-15/20R	(40) NEMA 5-15/20R	(2) NEMA 5-15/20R	(24) NEMA 5-15/20R
Rear Panel Receptacles	(12) NEMA 5-15/20R	(12) NEMA 5-15/20R	N/A	N/A	N/A	N/A	N/A	(8) NEMA 5-15/20R	N/A
Surge Protection									
Surge-protection Joule Rating	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Earth-ground Lug	Yes	Yes	No	No	No	No	No	Yes	Yes
Physical									
All-metal case	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Horizontal Installation	Yes	Yes	No	No	No	No	No	Yes	No
0U Vertical Installation	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Customization Options	1U, 0U, Wallmount, Under-counter	1U, 0U, Wallmount, Under-counter	0U, Wallmount, Under-counter	0U, Wallmount, Under-counter	0U, Wallmount, Under-counter	0U, Wallmount, Under-counter	0U, Wallmount, Under-counter	1U, 0U	0U, Wallmount
Warranty & Certifications									
62368-1 Certification	No	No	No	No	No	No	No	Yes	Yes
Other Certifications	RETIE, CSA, NOM, UL1363, ROHS	RETIE, CSA, NOM, UL1363, ROHS	CSA, NOM, UL60950-1, RoHS	RETIE, CSA, NOM, UL60950-1, RoHS	CSA, NOM, UL60950-1, RoHS	CSA, NOM, UL60950-1, RoHS	CSA, NOM, UL60950-1, RoHS	cUL, UL 1077, CE	cUL, UL 1077, CE
Warranty	5 Years	5 Years	5 Years	5 Years	2 Years	2 Years	2 Years	Lifetime	Lifetime

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

All names and trademarks are the property of the respective companies.

((Brand) Advantage in **BOLD**)
(MM Advantage in **BOLD**)

Feature Comparison Chart of MM OEPD Series vs. Tripp Lite PDU Series*

FEATURES	Tripp Lite Basic PDU Series					Minuteman OEPD Series	
	PDUH20DV	PDUH20HVL6	PDUNV	PDU12IEC	PDUV20HVL6-72	OEPD202L620HVN / -HW	OEPD2024IECHVI / -HW
Input							
On/Off Switch	No	No	No	No	No	No	No
Power On/Off LED	No	No	No	No	No	No	No
Input Power Cord Length	12-feet	15-feet	10-feet	N/A	10-feet	6-feet	6 feet
Input Connection	IEC320 C20 (w/L6-20P)	NEMA L6-20P	IEC C20 (w/5-15P, 5-20P, L5-20P, L6-20P, C14)	IEC C20	NEMA L6-20P	NEMA L6-20P / (-HW) Hardwire	NEMA L6-20P / (-HW) Hardwire
Input Circuit Breaker Protection	No	No	Yes	Yes	No	No	Yes
Input Voltage Range	100V-240V	208V-240V	120V-240V	120V-240V	208V-230V	200v-240V	200V-240V
Max Input Current	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps
Output							
Maximum Output Rating (A)	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps
Output Voltage Range	100V-240V	208V-240V	120V-240V	120V-240V	208V-230V	208V-240V	208V-240V
Max Capacity (W)	1600-3840 Watts	3,330-3,840 Watts	1920-3840 Watts	1920-3840 Watts	3,330-3,700 Watts	3840 Watts	3840 Watts
Number of Output Circuits	N/A	N/A	N/A	N/A	N/A	One	One
Front Panel Receptacles	(4) IEC320 C13	(4) IEC320 C13	(4) IEC320 C13	(4) IEC320 C13	(32) IEC320 C13 / (6) IEC320 C19	(2) NEMA L6-20R	(10) IEC320 C13 / (2) IEC320 C19
Rear Panel Receptacles	(8) IEC320 C13 / (2) IEC320 C19	(8) IEC320 C13 / (2) IEC320 C19	(8) IEC320 C13 / (2) IEC320 C19	(8) IEC320 C13 / (2) IEC320 C19	N/A	No	(10) IEC320 C13 / (2) IEC320 C19
Surge Protection							
Surge-protection Joule Rating	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Earth-ground Lug	Yes	Yes	Yes	Yes	No	No	No
Physical							
All-metal case	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Horizontal Installation	Yes	Yes	Yes	Yes	No	Yes	Yes
0U Vertical Installation	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Customization Options	1U, 0U, Wallmount, Under-counter	1U, 0U, Wallmount, Under-counter	1U, 0U, Wallmount, Under-counter	1U, 0U, Wallmount, Under-counter	0U, Wallmount, Under-counter	1U, 0U	1U, 0U
Warranty & Certifications							
62368-1 Certification	Yes	Yes	Yes	No	No	Yes	Yes
Other Certifications	CSA, NOM, ROHS, FCC Part 15 Class A	CSA, NOM, ROHS, FCC Part 15 Class A	CSA, RoHS, CE, FCC Part 15 Class A	RETIE, CSA, NOM, UL60950-1, RoHS, CE	RETIE, NOM, UL60950-1, RoHS	cETLus, CE	cETLus, CE
Warranty	5 Years	5 Years	5 Years	5 Years	5 Years	Lifetime	Lifetime

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

All names and trademarks are the property of the respective companies.

((Brand) Advantage in **BOLD**)
(MM Advantage in **BOLD**)

Feature Comparison Chart of MM OEPD Series vs. Tripp Lite PDU Series*

FEATURES	Tripp Lite Basic PDU Series				Minuteman OEPD Series	
	PDUH30HV19	PDUH30HV	PDU1230	PDUV30HV	OEPD302L630HVN / -HW	OEPD304L630HVN / -HW
Input						
On/Off Switch	No	No	No	No	No	No
Power On/Off LED	No	No	No	No	No	No
Input Power Cord Length	12-feet	12-feet	15-feet	10-feet	6 feet	6 feet
Input Connection	NEMA L6-30P	NEMA L6-30P	NEMA L6-30P	NEMA L6-30P	NEMA L6-30P / (-HW) Hardwire	NEMA L6-30P / (-HW) Hardwire
Input Circuit Breaker Protection	Yes, (2) 20 Amp	Yes, (2) 20 Amp	Yes, (4) 10 Amp, (4) 15 Amp	Yes, (2) 15 Amp	No	No
Input Voltage Range	200V-240V	200V-240V	200V-240V	208-230V	200V-240V	200V-240V
Max Input Current	24 Amps	24 Amps	24 Amps	24 Amps	24 Amps	24 Amps
Output						
Maximum Output Rating (A)	24 Amps	24 Amps	24 Amps (see breaker protection)	24 Amps	24 Amps	24 Amps
Output Voltage Range	200V-240V	200V-240V	200V-240V	208V-230V	200V-240V	200V-240V
Max Capacity (W)	4800-5800 Watts	4800-5800 Watts	4800-5800 Watts	5000-5500 Watts	5760 Watts	5760 Watts
Number of Output Circuits	N/A	N/A	N/A	N/A	N/A	(1) 30 Amp / (2) 20 Amp
Front Panel Receptacles	(4) IEC320 C19	(8) IEC320 C13	(4) IEC320 C13 / (4) IEC320 C19	(32) IEC320 C13 / (6) IEC320 C19	(2) NEMA L6-30R	(2) NEMA L6-20R / (2) NEMA L6-30R
Rear Panel Receptacles	N/A	(2) IEC320 C13	(12) IEC320 C13	N/A	N/A	N/A
Surge Protection						
Surge-protection Joule Rating	N/A	N/A	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A	N/A	N/A
Earth-ground Lug	Yes	Yes	Yes	No	N/A	N/A
Physical						
All-metal case	Yes	Yes	Yes	Yes	Yes	Yes
Horizontal Installation	Yes	Yes	Yes	No	Yes	Yes
0U Vertical Installation	Yes	Yes	Yes	Yes	Yes	Yes
Customization Options	1U, 0U, Wallmount, Undercounter	1U, 0U, Wallmount, Undercounter	1U, 0U, Wallmount, Undercounter	0U, Wallmount, Undercounter	1U, 0U	1U, 0U
Warranty & Certifications						
62368-1 Certification	Yes	Yes	Yes	Yes	Yes	Yes
Other Certifications	CSA, NOM, RoHS, FCC 15 Class A	CSA, NOM, RoHS, FCC 15 Class A	RETIE, CSA, NOM	CSA, NOM, RoHS	cETLus/CE	cETLus/CE
Warranty	2 Years	2 Years	5 Years	5 Years	Lifetime	Lifetime

All names and trademarks are the property of the respective companies.

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

((Brand) Advantage in **BOLD**)

(MM Advantage in **BOLD**)

Feature Comparison Chart of MM OEPD Series vs. VERTIV VP rPDU*

FEATURES	Vertiv VP rPDU Series		Minuteman OEPD Series				
	VP9562	VP9567	OEPD615HV	OEPD815HV	OEPD1415HV /-HW	OEPD1815V48	OEPD2415V62 /-HW
Input							
On/Off Switch	No	No	No	No	No	No	No
Power On/Off LED	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Input Power Cord Length	10-feet	10-feet	15-feet	15-feet	15-feet	15-feet	15-feet
Input Connection	NEMA 5-15P	NEMA 5-15P	NEMA 5-15P	NEMA 5-15P	NEMA 5-15P / (-HW) Hardwire	NEMA 5-15P	NEMA 5-15P / (-HW) Hardwire
Input Circuit Breaker Protection	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Input Voltage Range	100V-120V	100V-120V	120V	120V	120V	120V	120V
Max Input Current	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps
Output							
Maximum Output Rating (A)	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps
Output Voltage Range	100V-120V	100V-120V	120V	120V	120V	120V	120V
Max Capacity (W)	1,400 Watts	1,400 Watts	1440 Watts	1440 Watts	1440 Watts	1440 Watts	1440 Watts
Number of Output Circuits	N/A	N/A	One	One	One	One	One
Front Panel Receptacles	N/A	(14) NEMA 5-15R	N/A	(2) NEMA 5-15R	(6) NEMA 5-15R	(18) NEMA 5-15R	(24) NEMA 5-15R
Rear Panel Receptacles	(10) NEMA 5-15R	N/A	(6) NEMA 5-15R	(6) NEMA 5-15R	(8) NEMA 5-15R	N/A	N/A
Surge Protection							
Surge-protection Joule Rating	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Earth-ground Lug	No	No	Yes	Yes	Yes	Yes	Yes
Physical							
All-metal case	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Horizontal Installation	Yes	No	Yes	Yes	Yes	No	No
0U Vertical Installation	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Customization Options	1U, 0U	0U	1U, 0U	1U, 0U	1U, 0U	0U, Wallmount	0U, Wallmount
Warranty & Certifications							
62368-1 Certification	No	No	Yes	Yes	Yes	Yes	Yes
Other Certifications	UL60950-1, cUL, RoHS	UL60950-1, cUL, RoHS	cUL, UL1077, CE	cUL, UL1077, CE	cUL, UL1077, CE	cUL, UL1077, CE	cUL, UL1077, CE
Warranty	3 Years	3 Years	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime

All names and trademarks are the property of the respective companies.

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

((Brand) Advantage in **BOLD**)

(MM Advantage in **BOLD**)

Feature Comparison Chart of MM OEPD Series vs. VERTIV VP rPDU Series*

FEATURES	Vertiv VP rPDU	Minuteman OEPD Series	
	VP9563	OEPD1020HV /-HW	OEPD2420V62 /-L /-HW
Input			
On/Off Switch	No	No	No
Power On/Off LED	Yes	Yes	Yes
Input Power Cord Length	10-feet	15-feet	15-feet
Input Connection	NEMA 5-20P	NEMA 5-20P	NEMA 5-20P / (-L) L5-20P / (-HW) Hardwire
Input Circuit Breaker Protection	Yes	Yes	Yes
Input Voltage Range	100V-120V	120V	120V
Max Input Current	16 Amps	20 Amps	20 Amps
Output			
Maximum Output Rating (A)	16 Amps	16 Amps	16 Amps
Output Voltage Range	100V-120V	120V	120V
Max Capacity (W)	1,900 Watts	1920 Watts	1920 Watts
Number of Output Circuits	N/A	One	One
Front Panel Receptacles	N/A	(2) NEMA 5-15/20R	(24) NEMA 5-15/20R
Rear Panel Receptacles	(10) NEMA 5-20R	(8) NEMA 5-15/20R	N/A
Surge Protection			
Surge-protection Joule Rating	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A
Earth-ground Lug	No	Yes	Yes
Physical			
All-metal case	Yes	Yes	Yes
Horizontal Installation	Yes	Yes	No
0U Vertical Installation	Yes	Yes	Yes
Customization Options	1U, 0U	1U, 0U	0U, Wallmount
Warranty & Certifications			
62368-1 Certification	No	Yes	Yes
Other Certifications	UL60950-1, cUL, RoHS	cUL, UL 1077, CE	cUL, UL 1077, CE
Warranty	3 Years	Lifetime	Lifetime

All names and trademarks are the property of the respective companies.

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

((Brand) Advantage in **BOLD**)

(MM Advantage in **BOLD**)

Feature Comparison Chart of MM OEPD Series vs. VERTIV VP rPDU Series*

FEATURES	Vertiv VP rPDU Series		Minuteman OEPD Series	
	VP9571A	VP7541	OEPD302L630HVN /-HW	OEPD304L630HVN /-HW
Input				
On/Off Switch	Yes	Yes	No	No
Power On/Off LED	Yes	Yes	No	No
Input Power Cord Length	10-feet	10-feet	6 feet	6 feet
Input Connection	NEMA L6-30P	NEMA L6-30P	NEMA L6-30P / (-HW) Hardwire	NEMA L6-30P / (-HW) Hardwire
Input Circuit Breaker Protection	Yes, (2) 20 Amp	Yes, (2) 20 Amp	No	No
Input Voltage Range	200V-240V	200V-240V	200V-240V	200V-240V
Max Input Current	24 Amps	24 Amps	24 Amps	24 Amps
Output				
Maximum Output Rating (A)	15 Amp (Per Outlet)	15 Amp (per C13), 20 Amp (per C19)	24 Amps	24 Amps
Output Voltage Range	200V-240V	200V-240V	200V-240V	200V-240V
Max Capacity (W)	4900 Watts	4900 Watts	5760 Watts	5760 Watts
Number of Output Circuits	N/A	N/A	N/A	(1) 30 Amp / (2) 20 Amp
Front Panel Receptacles	N/A	(20) IEC320 C13 / (4) IEC320 C19	(2) NEMA L6-30R	(2) NEMA L6-20R / (2) NEMA L6-30R
Rear Panel Receptacles	(12) IEC320 C13	N/A	N/A	N/A
Surge Protection				
Surge-protection Joule Rating	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A
Earth-ground Lug	No	No	N/A	N/A
Physical				
All-metal case	Yes	Yes	Yes	Yes
Horizontal Installation	Yes	No	Yes	Yes
0U Vertical Installation	Yes	Yes	Yes	Yes
Customization Options	1U, 0U	0U	1U, 0U	1U, 0U
Warranty & Certifications				
62368-1 Certification	No	No	Yes	Yes
Other Certifications	UL60950-1, cUL, RoHS	UL60950-1, cUL, RoHS	cETLus/CE	cETLus/CE
Warranty	3 Years	3 Years	Lifetime	Lifetime

All names and trademarks are the property of the respective companies.

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

((Brand) Advantage in **BOLD**)

((MM Advantage in **BOLD**)

Feature Comparison Chart of MM OEPD Series vs. EATON PDU SERIES*

FEATURES	Eaton PDU Series				Minuteman OEPD Series				
	T8-A-S	TPC12F-A-CB	EPBZ73	EPBZ98	OEPD615HV	OEPD815HV	OEPD1415HV /-HW	OEPD1815V48	OEPD2415V62 /-HW
Input									
On/Off Switch	N/A	Yes	No	No	No	No	No	No	No
Power On/Off LED	N/A	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Input Power Cord Length	9-feet	9-feet	15-feet	6-feet	15-feet	15-feet	15-feet	15-feet	15-feet
Input Connection	(2) NEMA 5-15P	NEMA 5-15P	NEMA 5-15P	NEMA 5-15P	NEMA 5-15P	NEMA 5-15P	NEMA 5-15P / (-HW) Hardwire	NEMA 5-15P	NEMA 5-15P / (-HW) Hardwire
Input Circuit Breaker Protection	N/A	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Input Voltage Range	120V	110V-125V	100V-120V	110V-125V	120V	120V	120V	120V	120V
Max Input Current	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps
Output									
Maximum Output Rating (A)	N/A	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps
Output Voltage Range	120V	120V	100V-120V	110V-125V	120V	120V	120V	120V	120V
Max Capacity (W)	1440 Watts	1440 Watts	1440 Watts	1440 Watts	1440 Watts	1440 Watts	1440 Watts	1440 Watts	1440 Watts
Number of Output Circuits	N/A	N/A	N/A	N/A	One	One	One	One	One
Front Panel Receptacles	(8) NEMA 5-15R	(4) NEMA 5-15R	(18) NEMA 5-15R	(18) NEMA 5-15R	N/A	(2) NEMA 5-15R	(6) NEMA 5-15R	(18) NEMA 5-15R	(24) NEMA 5-15R
Rear Panel Receptacles	N/A	(8) NEMA 5-15R	N/A	N/A	(6) NEMA 5-15R	(6) NEMA 5-15R	(8) NEMA 5-15R	N/A	N/A
Surge Protection									
Surge-protection Joule Rating	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Earth-ground Lug	N/A	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Physical									
All-metal case	N/A	Yes	Yes	N/A	Yes	Yes	Yes	Yes	Yes
Horizontal Installation	Yes	Yes	No	Yes	Yes	Yes	Yes	No	No
0U Vertical Installation	No	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Customization Options	1U	1U	0U Vertical	1U, 0U	1U, 0U	1U, 0U	1U, 0U	0U, Wallmount	0U, Wallmount
Warranty & Certifications									
62368-1 Certification	N/A	N/A	No	No	Yes	Yes	Yes	Yes	Yes
Other Certifications	N/A	UL	UL60950, cUL, UL	UL 60950	cUL, UL1077, CE	cUL, UL1077, CE	cUL, UL1077, CE	cUL, UL1077, CE	cUL, UL1077, CE
Warranty	3 Years	3 Years	3 Years	3 Years	Lifetime	Lifetime	Lifetime	Lifetime	Lifetime

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

All names and trademarks are the property of the respective companies.

((Brand) Advantage in **BOLD**)

(MM Advantage in **BOLD**)

Feature Comparison Chart of MM OEPD Series vs. EATON PDU Series*

FEATURES	Eaton PDU Series							Minuteman OEPD Series	
	TPC3225	TPC12F-A2	PW102 BA1U158	PW102BAU159	EPBZ72	EPBZ77	EPBZ96	OEPD1020HV / -HW	OEPD2420V62 /-L /-HW
Input									
On/Off Switch	No	Yes	Yes	Yes	No	No	No	No	No
Power On/Off LED	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Input Power Cord Length	15-foot	9-foot	9-foot	9-foot	15-foot	15-foot	6-foot	15-foot	15-foot
Input Connection	N/A	NEMA 5-20P	NEMA 5-20P	NEMA L5-20P	NEMA L5-20P	NEMA L5-20P (W/5-20P Adaptor)	NEMA L5-20P	NEMA 5-20P	NEMA 5-20P / (-L) L5-20P / (-HW) Hardwire
Input Circuit Breaker Protection	Yes (5: 6, 6, 6, 4 Amps)	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Input Voltage Range	120V	110V-125V	110V-125V	110V-125V	100V-120V	100V-120V	110V-125V	120V	120V
Max Input Current	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps	20 Amps	20 Amps
Output									
Maximum Output Rating (A)	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps
Output Voltage Range	120V	110V-125V	110V-125V	110V-125V	100V-120V	100V-120V	110V-125V	120V	120V
Max Capacity (W)	N/A	1920 Watts	1920 Watts	1920 Watts	1920 Watts	1920 Watts	1920 Watts	1920 Watts	1920 Watts
Number of Output Circuits	N/A	N/A	N/A	N/A	N/A	N/A	N/A	One	One
Front Panel Receptacles	N/A	(4) NEMA 5-20R	(10) NEMA 5-20R	(10) NEMA 5-20R	(18) NEMA 5-20R	(24) NEMA 5-20R	(24) NEMA 5-20R	(2) NEMA 5-15/20R	(24) NEMA 5-15/20R
Rear Panel Receptacles	(10) NEMA 5-15R	(8) NEMA 5-20R	(2) NEMA 5-20R	(2) NEMA 5-20R	N/A	N/A	N/A	(8) NEMA 5-15/20R	N/A
Surge Protection									
Surge-protection Joule Rating	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Earth-ground Lug	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Physical									
All-metal case	Yes	Yes	Yes	Yes	N/A	N/A	N/A	Yes	Yes
Horizontal Installation	Yes	Yes	Yes	Yes	No	No	No	Yes	No
0U Vertical Installation	No	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Customization Options	1U	1U	0U, 1U	0U, 1U	0U	0U	0U	1U, 0U	0U, Wallmount
Warranty & Certifications									
52368-1 Certification	No	No	No	No	No	No	No	Yes	Yes
Other Certifications	UL	UL, cUL	UL, cUL, RoHS	UL, cUL, RoHS	UL60950-1, UL1077	UL60950-1, UL1077	UL 60950	cUL, UL1077, CE	cUL, UL1077, CE
Warranty	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years	Lifetime	Lifetime

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes. All names and trademarks are the property of the respective companies.

((Brand) Advantage in **BOLD**)
(MM Advantage in **BOLD**)

Feature Comparison Chart of MM OEPD Series vs. Eaton PDU Series*

FEATURES	Eaton PDU Series		Minuteman OEPD Series	
	PW105BA2U420	EBA110-10	OEPD302L630HVN /-HW	OEPD304L630HVN /-HW
Input				
On/Off Switch	N/A	No	No	No
Power On/Off LED	N/A	No	No	No
Input Power Cord Length	9-feet	10-feet	6 feet	6 feet
Input Connection	L6-30P	L6-30P	NEMA L6-30P / (-HW) Hardwire	NEMA L6-30P / (-HW) Hardwire
Input Circuit Breaker Protection	N/A	Yes, (2) 20 Amp	No	No
Input Voltage Range	200V-240V	200V-240V	200V-240V	200V-240V
Max Input Current	24 Amps	24 Amps	24 Amps	24 Amps
Output				
Maximum Output Rating (A)	N/A	24 Amps	24 Amps	24 Amps
Output Voltage Range	200V-240V	200V-240V	200V-240V	200V-240V
Max Capacity (W)	4990 Watts	1920 Watts	5760 Watts	5760 Watts
Number of Output Circuits	N/A	N/A	N/A	(1) 30 Amp / (2) 20 Amp
Front Panel Receptacles	(4) NEMA L6-30P	(24) IEC320 C13 / (6) IEC320 C19	(2) NEMA L6-30R	(2) NEMA L6-20R / (2) NEMA L6-30R
Rear Panel Receptacles	N/A	N/A	N/A	N/A
Surge Protection				
Surge-protection Joule Rating	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A
Earth-ground Lug	N/A	No	N/A	N/A
Physical				
All-metal case	N/A	Yes	Yes	Yes
Horizontal Installation	Yes	Yes	Yes	Yes
0U Vertical Installation	No	Yes	Yes	Yes
Customization Options	2U	1U, 0U	1U, 0U	1U, 0U
Warranty & Certifications				
62368-1 Certification	No	No	Yes	Yes
Other Certifications	UL60950-1, UL, cUL, RoHS	cULus, RoHS2	cETLus/CE	cETLus/CE
Warranty	3 Years	3 Years	Lifetime	Lifetime

All names and trademarks are the property of the respective companies.

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

((Brand) Advantage in **BOLD**)

(MM Advantage in **BOLD**)

Feature Comparison Chart of MM OEPD Series vs. CHATSWORTH PRODUCTS BASIC PDU*

FEATURES	Chatsworth Basic PDU Series			Minuteman OEPD Series	
	E0-1401-C /-E /-CE	E0-1243-C /-E /-CE	E0-1001-C /-E /-CE	OEPD1020HV /-HW	OEPD2420V62 /-L /-HW
Input					
On/Off Switch	No	No	No	No	No
Power On/Off LED	No	No	No	Yes	Yes
Input Power Cord Length	10-feet	10-feet	10-feet	15-feet	15-feet
Input Connection	IEC320 C20 to NEMA L5-20P	IEC320 C20 to NEMA L5-20P	IEC320 C20 to NEMA L5-20P	NEMA 5-20P	NEMA 5-20P / (-L) L5-20P / (-HW) Hardwire
Input Circuit Breaker Protection	Yes	Yes	Yes	Yes	Yes
Input Voltage Range	120V	120V	120V	120V	120V
Max Input Current	16 Amps	16 Amps	16 Amps	20 Amps	20 Amps
Output					
Maximum Output Rating (A)	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps
Output Voltage Range	120V	120V	120V	120V	120V
Max Capacity (W)	1920 Watts	1920 Watts	1920 Watts	1920 Watts	1920 Watts
Number of Output Circuits	N/A	N/A	N/A	One	One
Front Panel Receptacles	N/A	N/A	N/A	(2) NEMA 5-15/20R	(24) NEMA 5-15/20R
Rear Panel Receptacles	(24) NEMA 5-20R	(12) NEMA 5-20R	(24) NEMA 5-20R	(8) NEMA 5-15/20R	N/A
Surge Protection					
Surge-protection Joule Rating	N/A	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A	N/A
Earth-ground Lug	Yes	Yes	Yes	Yes	Yes
Physical					
All-metal case	N/A	N/A	N/A	Yes	Yes
Horizontal Installation	Yes	Yes	No	Yes	No
0U Vertical Installation	No	No	Yes	Yes	Yes
Customization Options	2U	1U	0U	1U, 0U	0U, Wallmount
Warranty & Certifications					
62368-1 Certification	Yes	Yes	Yes	Yes	Yes
Other Certifications	UL, CE, RoHS, FCC Part 15 Class A, EN 55022	UL, CE, RoHS, FCC Part 15 Class A, EN 55022	UL, CE, RoHS, FCC Part 15 Class A, EN 55022	cUL, UL1077, CE	cUL, UL1077, CE
Warranty	3 Years	3 Years	3 Years	Lifetime	Lifetime

All names and trademarks are the property of the respective companies.

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

((Brand) Advantage in **BOLD**)

(MM Advantage in **BOLD**)

Feature Comparison Chart of MM OEPD Series vs. CHATSWORTH PRODUCTS BASIC PDU*

FEATURES	Chatsworth Basic PDU Series					Minuteman OEPD Series	
	E0-1270-C /-E /-CE	E0-1245-C /-E /-CE	E0-1003-C /-E /-CE	E0-1403-C /-E /-CE	E0-1459-C /-E /-CE	OEPD2021620HVN / -HW	OEPD2024IECHVI /-HW
Input							
On/Off Switch	No	No	No	No	No	No	No
Power On/Off LED	No	No	No	No	No	No	No
Input Power Cord Length	10-feet	10-feet	10-feet	10-feet	10-feet	6-feet	6 feet
Input Connection	IEC320 C20 to NEMA L6-20P	IEC320 C20 to NEMA L6-20P	IEC320 C20 to NEMA L6-20P	IEC320 C20 to NEMA L6-20P	IEC320 C20 to NEMA L6-20P	NEMA L6-20P / (-HW) Hardwire	NEMA L6-20P / (-HW) Hardwire
Input Circuit Breaker Protection	Yes	Yes	Yes	Yes	Yes	No	Yes
Input Voltage Range	208V	208V	208V	208V	208V	200v-240V	200v-240V
Max Input Current	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps
Output							
Maximum Output Rating (A)	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps
Output Voltage Range	208V	208V	208V	208V	208V	208V-240V	208V-240V
Max Capacity (W)	3330 Watts	3330 Watts	3330 Watts	3330 Watts	3330 Watts	3840 Watts	3840 Watts
Number of Output Circuits	N/A	N/A	N/A	N/A	N/A	One	One
Front Panel Receptacles	N/A	N/A	(24) C13	N/A	N/A	(2) NEMA L6-20R	(10) IEC320 C13 / (2) IEC320 C19
Rear Panel Receptacles	(8) IEC320 C13 / (4) IEC320 C19 (Locking)	(12) IEC320 C13	N/A	(24) IEC320 C13 (Locking)	(18) IEC320 C13 / (6) IEC320 C19 (Locking)	No	(10) IEC320 C13 / (2) IEC320 C19
Surge Protection							
Surge-protection Joule Rating	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Earth-ground Lug	Yes	Yes	Yes	Yes	Yes	No	No
Physical							
All-metal case	N/A	N/A	N/A	N/A	N/A	Yes	Yes
Horizontal Installation	Yes	Yes	No	Yes	Yes	Yes	Yes
0U Vertical Installation	No	No	Yes	No	No	Yes	Yes
Customization Options	1U	1U	0U	2U	2U	1U, 0U	1U, 0U
Warranty & Certifications							
	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Other Certifications	UL, CE, RoHS, FCC Part 15 Class A, EN 55022	UL, CE, RoHS, FCC Part 15 Class A, EN 55022	UL, CE, RoHS, FCC Part 15 Class A, EN 55022	UL, CE, RoHS, FCC Part 15 Class A, EN 55022	UL, CE, RoHS, FCC Part 15 Class A, EN 55022	cETLus, CE	cETLus, CE
Warranty	3 Years	3 Years	3 Years	3 Years	3 Years	Lifetime	Lifetime

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

All names and trademarks are the property of the respective companies.

((Brand) Advantage in **BOLD**)

(MM Advantage in **BOLD**)

Feature Comparison Chart of MM OEPD Series vs. CHATSWORTH PRODUCTS BASIC PDU*

FEATURES	Chatsworth Basic PDU Series									Minuteman OEPD Series	
	E0-1253-C /-E /-CE	E0-1246-C /-E /-CE	E0-1271-C /-E /-CE	E0-1478-C /-E /-CE	E0-1004-C /-E /-CE	E0-1404-C /-E /-CE	E0-1461-C /-E /-CE	E0-1015-C /-E /-CE		OEPD302L630HVN /-HW	OEPD304L630HVN /-HW
Input											
On/Off Switch	No	No	No	No	No	No	No	No	No	No	No
Power On/Off LED	No	No	No	No	No	No	No	No	No	No	No
Input Power Cord Length	10-feet	10-feet	10-feet	10-feet	10-feet	10-feet	10-feet	10-feet	10-feet	6 feet	6 feet
Input Connection	NEMA L6-30P	NEMA L6-30P	NEMA L6-30P	NEMA L6-30P	NEMA L6-30P	NEMA L6-30P	NEMA L6-30P	NEMA L6-30P	NEMA L6-30P	NEMA L6-30P / (-HW) Hardwire	NEMA L6-30P / (-HW) Hardwire
Input Circuit Breaker Protection	Yes, (2) 20 Amp	Yes, (2) 20 Amp	Yes, (2) 20 Amp	Yes, (2) 20 Amp	Yes, (2) 20 Amp	Yes, (2) 20 Amp	Yes, (2) 20 Amp	Yes, (2) 20 Amp	Yes, (2) 20 Amp	No	No
Input Voltage Range	208V	208V	208V	208V	208V	208V	208V	208V	208V	200V-240V	200V-240V
Max Input Current	24 Amps	24 Amps	24 Amps	24 Amps	24 Amps	24 Amps	24 Amps	24 Amps	24 Amps	24 Amps	24 Amps
Output											
Maximum Output Rating (A)	24 Amps	24 Amps	24 Amps	24 Amps	24 Amps	24 Amps	24 Amps	24 Amps	24 Amps	24 Amps	24 Amps
Output Voltage Range	208V	208V	208V	208V	208V	208V	208V	208V	208V	200V-240V	200V-240V
Max Capacity (W)	4990 Watts	4990 Watts	4990 Watts	4990 Watts	4990 Watts	4990 Watts	4990 Watts	4990 Watts	4990 Watts	5760 Watts	5760 Watts
Number of Output Circuits	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	(1) 30 Amp / (2) 20 Amp
Front Panel Receptacles	N/A	N/A	N/A	N/A	(24) IEC320 C19 (Locking)	(24) IEC320 C19 (Locking)	(18) IEC320 C13 / (6) IEC320 C19 (Locking)	(36) IEC320 C13 / (6) IEC320 C19 (Locking)		(2) NEMA L6-30R	(2) NEMA L6-20R / (2) NEMA L6-30R
Rear Panel Receptacles	(9) IEC320 C19 (Locking)	(12) IEC320 C13 (Locking)	(8) IEC320 C13 / (4) IEC320 C19 (Locking)	(6) IEC320 C13 / (12) IEC320 C19 (Locking)	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Surge Protection											
Surge-protection Joule Rating	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Earth-ground Lug	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	N/A	N/A
Physical											
All-metal case	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	Yes	Yes
Horizontal Installation	Yes	Yes	Yes	Yes	No	Yes	Yes	No	No	Yes	Yes
0U Vertical Installation	No	No	No	No	Yes	No	No	Yes	Yes	Yes	Yes
Customization Options	1U	1U	1U	2U	0U	2U	2U	0U	0U	1U, 0U	1U, 0U
Warranty & Certifications											
62368-1 Certification	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Other Certifications	UL, CE, RoHS, FCC Part 15 Class A, EN 55022	UL, CE, RoHS, FCC Part 15 Class A, EN 55022	UL, CE, RoHS, FCC Part 15 Class A, EN 55022	UL, CE, RoHS, FCC Part 15 Class A, EN 55022	UL, CE, RoHS, FCC Part 15 Class A, EN 55022	UL, CE, RoHS, FCC Part 15 Class A, EN 55022	UL, CE, RoHS, FCC Part 15 Class A, EN 55022	UL, CE, RoHS, FCC Part 15 Class A, EN 55022	UL, CE, RoHS, FCC Part 15 Class A, EN 55022	cETLus/CE	cETLus/CE
Warranty	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years	Lifetime	Lifetime

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

((Brand) Advantage in **BOLD**)
(MM Advantage in **BOLD**)

All names and trademarks are the property of the respective companies.