

Feature Comparison Chart of MM RPM Series vs. APC AP Series*

FEATURES	APC AP Series		Minuteman RPM Series				
	AP7900B	AP8931	RPM1521E	RPM1581HVN	RPM158N1LCD-HW (-15P /-IEC)	RPM1516N1LCD-HW (15P /-IEC)	RPM1524N1LCD-HW (-15P /-IEC)
Input							
On/Off Switch	No	No	Yes	No	No	No	No
Power On/Off LED	No	No	Yes	Yes	Yes	Yes	Yes
Input Voltage	100V-120V	100V-120V	120V	100V-120V	100V-127V	100V-127V	100V-127V
Input Plug (Cord Length)	NEMA 5-15P (12-ft)	NEMA 5-15P (10-ft)	NEMA 5-15P (6-ft)	NEMA 5-15P (10-ft)	Hardwire (10-ft) NEMA 5-15P (10-ft) IEC C20 (10-ft)	Hardwire (10-ft) NEMA 5-15P (10-ft) IEC C20 (10-ft)	Hardwire (10-ft) NEMA 5-15P (10-ft) IEC C20 (10-ft)
Input Protection	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Hydraulic-Magnetic Breakers	Yes	Yes	No	No	No	No	No
Max Input Current (A)	15 Amps	15 Amps	15 Amps	15 Amps	15 Amps	15 Amps	15 Amps
Surge-protection Joule Rating	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Earth-ground Lug	No	No	No	No	Yes	Yes	Yes
Output							
Output Voltage	100V-120V	100V-120V	120V	100V-120V	100V-127V	100V-127V	100V-127V
Maximum Output Rating (A)	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps
Number of Output Circuits	N/A	N/A	N/A	One	One	One	One
Front Panel Receptacles (Qty)	(8) NEMA 5-15R	(8) NEMA 5-15R	N/A	(8) NEMA 5-15R	N/A	N/A	N/A
Rear Panel Receptacles (Qty)	N/A	N/A	(2) NEMA 5-15R	N/A	(8) NEMA 5-15R	(16) NEMA 5-15R	(24) NEMA 5-15R
Management							
Web & SNMP Management	Yes	Yes	Yes	Yes	Yes	Yes	Yes
10/100/1000 Mbit Compatible	10/100	10/100	N/A	N/A	10/100	10/100	10/100
Network port Sharing	No	Yes	Yes	Yes	Yes	Yes	Yes
Individual Outlet Control	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Individual Outlet Metering	No	No	No	No	No	No	No
Combined Outlet Metering	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Multi-level User Access	Yes	Yes	Yes	Yes	Yes	Yes	Yes
On/Off Outlet Sequencing	Yes	Yes	Yes	Yes	Yes	Yes	Yes
On/Off Outlet Scheduling	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Event Configuration	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Outlet Grouping	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Auto Ping Function	N/A	N/A	Yes	Yes	Yes	Yes	Yes
SNMP IPv4/IPv6 Compatible	Yes	Yes	No	No	Yes	Yes	Yes
SNMPv3 Compatible	N/A	N/A	Yes	Yes	Yes	Yes	Yes
SSH/SSL Compatible	N/A	Yes	Yes	Yes	Yes	Yes	Yes
TLS v1.2 or Greater	N/A	N/A	Yes	Yes	Yes	Yes	Yes
Env. Sensor Compatible	No	Yes	Yes	Yes	Yes	Yes	Yes
Flash Firmware Upgrades	No	Yes	Yes	Yes	Yes	Yes	Yes
Remote Batch Updates	No	N/A	N/A	N/A	N/A	N/A	N/A
Physical							
All-metal case	N/A	N/A	Yes	Yes	Yes	Yes	Yes
Installation Format (H/V)	Horizontal 1U	Vertical 0U	Horizontal	Horizontal (1U), Vertical (0U)	Horizontal (1U), Vertical (0U)	Vertical (0U)	Vertical (0U)
Color-coded Receptacles	No	No	No	No	No	No	No
Dimensions (HxWxD)	1.73" x 17.50" x 4.25"	38.9" x 2.18" x 1.82"	1.7" x 4.9" x 7.17"	1.73" x 17" x 3.54"	1.75" x 5.83" x 17.01"	49.02" x 2.20" x 3.07"	70.00" x 2.20" x 3.07"
Weight	5 lbs.	9.1 lbs.	1.78 lbs.	4.85 lbs.	7.72 lbs.	8.82 lbs.	13.22 lbs.
Warranty & Certifications							
62368-1 Certification	N/A	No	No	Yes	Yes	Yes	Yes
RoHS Compliant	N/A	Yes	Yes	No	Yes	Yes	Yes
TAA Compliant	N/A	No	Yes	Yes	Yes	Yes	Yes
Warranty	2 Years	2 Years	3 Years	3 Years	3 Years	3 Years	3 Years

All names and trademarks are the property of the respective companies.

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

(Competitor) Advantage in **BOLD**

(MM Advantage in **BOLD**)

Feature Comparison Chart of MM RPM Series vs. APC AP Series*

FEATURES	AP Series		Minuteman RPM Series		
	AP7901B	AP8930	RPM208N1LCD-HW (-20P /-L20P /-IEC)	RPM2016N1LCD-HW (-20P/-L20P/-IEC)	RPM2024N1LCD-HW (-20P/-L20P/-IEC)
Input					
On/Off Switch	No	No	No	No	No
Power On/Off LED	No	No	Yes	Yes	Yes
Input Voltage	100V-120V	100V-120V	100V-127V	100V-127V	100V-127V
Input Plug (Cord Length)	NEMA L5-20P (12-ft)	NEMA L5-20P (10-ft)	Hardwire (10-ft) NEMA 5-20P (10-ft) NEMA L5-20P (10-ft) IEC320 C20 (10-ft)	Hardwire (10-ft) NEMA 5-20P (10-ft) NEMA L5-20P (10-ft) IEC320 C20 (10-ft)	Hardwire (10-ft) NEMA 5-20P (10-ft) NEMA L5-20P (10-ft) IEC320 C20 (10-ft)
Input Protection	Yes	Yes	Yes	Yes	Yes
Hydraulic-Magnetic Breakers	Yes	Yes	No	No	No
Max Input Current (A)	20 Amps	20 Amps	20 Amps	20 Amps	20 Amps
Surge-protection Joule Rating	N/A	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A	N/A
Earth-ground Lug	No	No	Yes	Yes	Yes
Output					
Output Voltage	100V-120V	100V-120V	100V-127V	100V-127V	100V-127V
Maximum Output Rating (A)	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps
Number of Output Circuits	N/A	N/A	One	One	One
Front Panel Receptacles (Qty)	(8) NEMA 5-20R	(24) NEAM 5-20R	N/A	(16) NEMA 5-15/20R	(24) NEMA 5-15/20R
Rear Panel Receptacles (Qty)	N/A	N/A	(8) NEMA 5-15/20R	N/A	N/A
Management					
Web & SNMP Management	Yes	Yes	Yes	Yes	Yes
10/100/1000 Mbit Compatible	10/100	10/100	10/100	10/100	10/100
Network port Sharing	No	Yes	Yes	Yes	Yes
Individual Outlet Control	Yes	Yes	Yes	Yes	Yes
Individual Outlet Metering	No	No	No	No	No
Combined Outlet Metering	Yes	Yes	Yes	Yes	Yes
Multi-level User Access	Yes	Yes	Yes	Yes	Yes
On/Off Outlet Sequencing	Yes	Yes	Yes	Yes	Yes
On/Off Outlet Scheduling	Yes	Yes	Yes	Yes	Yes
Event Configuration	Yes	Yes	Yes	Yes	Yes
Outlet Grouping	Yes	Yes	Yes	Yes	Yes
Auto Ping Function	N/A	N/A	Yes	Yes	Yes
SNMP IPv4/IPv6 Compatible	Yes	Yes	Yes	Yes	Yes
SNMPv3 Compatible	N/A	N/A	Yes	Yes	Yes
SSH/SSL Compatible	Yes	Yes	Yes	Yes	Yes
TLS v1.2 or Greater	Yes	N/A	Yes	Yes	Yes
Env. Sensor Compatible	No	Yes	Yes	Yes	Yes
Flash Firmware Upgrades	No	Yes	Yes	Yes	Yes
Remote Batch Updates	No	N/A	N/A	N/A	N/A
Physical					
All-metal case	N/A	N/A	Yes	Yes	Yes
Installation Format (H/V)	Horizontal (1U)	Vertical (0U)	Horizontal (1U), Vertical (0U)	Vertical (0U)	Vertical (0U)
Color-coded Receptacles	No	No	No	No	No
Dimensions (HxWxD)	1.73" x 17.5" x 4.25"	70.5" x 2.18" x 1.82"	1.75" x 17.01" x 5.83"	49.02" x 2.20" x 3.07"	70.00" x 2.20" x 3.07"
Weight	5 lbs.	14.3 lbs.	7.72 lbs.	8.82 lbs.	13.22 lbs.
Warranty & Certifications					
62368-1 Certification	No	No	Yes	Yes	Yes
RoHS Compliant	Yes	Yes	Yes	Yes	Yes
TAA Compliant	No	N/A	Yes	Yes	Yes
Warranty	2 Years	2 Years	3 Years	3 Years	3 Years

All names and trademarks are the property of the respective companies.

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

(Competitor) Advantage in **BOLD**)

(MM Advantage in **BOLD**)

Feature Comparison Chart of MM RPM Series vs. (Competitor) Series*

	AP Series		Minuteman RPM Series		
	AP7902B	AP8932 (US)	RPM308N1LCD-HW (-L30P)	RPM3016N1LCD-HW (-L30P)	RPM3024N1LCD -HW (-L30P)
Input					
On/Off Switch	No	No	No	No	No
Power On/Off LED	No	No	Yes	Yes	Yes
Input Voltage	100V-120V	100V-120V	100V-127V	100V-127V	100V-127V
Input Plug (Cord Length)	NEMA L5-30P (12-ft)	NEMA L5-30P (10-ft)	Hardwire (10-ft) NEMA L6-30P (10-ft)	Hardwire (10-ft) NEMA L6-30P (10-ft)	Hardwire (10-ft) NEMA L6-30P (10-ft)
Input Protection	Yes, (2) 20 Amp Breakers	Yes	Yes	Yes	Yes
Hydraulic-Magentic Breakers	Yes	Yes	No	No	No
Max Input Current (A)	30 Amps	30 Amps	30 Amps	30 Amps	30 Amps
Surge-protection Joule Rating	N/A	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A	N/A
Earth-ground Lug	No	No	Yes	Yes	Yes
Output					
Output Voltage	100V-120V	100V-120V	100V-127V	100V-127V	100V-127V
Maximum Output Rating (A)	24 Amps	24 Amps	24 Amps	24 Amps	24 Amps
Number of Output Circuits	N/A	N/A	One	One	One
Front Panel Receptacles (Qty)	(16) NEMA 5-20R	(24) NEMA 5-20R	N/A	(16) NEMA 5-15/20R	(24) NEMA 5-15/20R
Rear Panel Receptacles (Qty)	N/A	N/A	(8) NEMA 5-15/20R	N/A	N/A
Management					
Web & SNMP Management	Yes	Yes	Yes	Yes	Yes
10/100/1000 Mbit Compatible	10/100	10/100	10/100	10/100	10/100
Network port Sharing	No	Yes	Yes	Yes	Yes
Individual Outlet Control	Yes	Yes	Yes	Yes	Yes
Individual Outlet Metering	No	No	No	No	No
Combined Outlet Metering	Yes	Yes	Yes	Yes	Yes
Multi-level User Access	Yes	Yes	Yes	Yes	Yes
On/Off Outlet Sequencing	Yes	Yes	Yes	Yes	Yes
On/Off Outlet Scheduling	Yes	Yes	Yes	Yes	Yes
Event Configuration	Yes	Yes	Yes	Yes	Yes
Outlet Grouping	Yes	Yes	Yes	Yes	Yes
Auto Ping Function	N/A	N/A	Yes	Yes	Yes
SNMP IPv4/IPv6 Compatible	Yes	Yes	Yes	Yes	Yes
SNMPv3 Compatible	N/A	N/A	Yes	Yes	Yes
SSH/SSL Compatible	Yes	Yes	Yes	Yes	Yes
TLS v1.2 or Greater	Yes	N/A	Yes	Yes	Yes
Env. Sensor Compatible	No	Yes	Yes	Yes	Yes
Flash Firmware Upgrades	No	Yes	Yes	Yes	Yes
Remote Batch Updates	No	N/A	N/A	N/A	N/A
Physical					
All-metal case	N/A	N/A	Yes	Yes	Yes
Installation Format (H/V)	Horizontal 2U	Vertical/0U	Horizontal/1U, Vertical/0U	Vertical (0U)	Vertical (0U)
Color-coded Receptacles	No	No	No	No	No
Dimensions (HxWxD)	3.5" x 17.5" x 4.5"	78.9" x 6.48" x 4.26"	1.76" x 17.00" x 8.50"	49.02" x 2.20" x 3.54"	70.00" x 2.20" x 3.54"
Weight	9.9 lbs.	17.27 lbs.	8.22 lbs.	9.26 lbs.	17.63 lbs.
Warranty & Certifications					
62368-1 Certification	No	No	Yes	Yes	Yes
RoHS Compliant	Yes	Yes	Yes	Yes	Yes
TAA Compliant	No	No (Yes)	Yes	Yes	Yes
Warranty	2 Years	2 Years	3 Years	3 Years	3 Years

and trademarks are the property of the respective companies.

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

(Competitor) Advantage in **BOLD**

(MM Advantage in **BOLD**)

Feature Comparison Chart of MM RPM Series vs. APC AP Series*

FEATURES	AP Series		Minuteman RPM Series			
	AP7921B	AP8958NA3	RPM204I2LCD (-HW/-L20P)	RPM208I2LCD-L20P (-HW/-L20P)	RPM2016I2LCD-L20P (-HW/-L20P)	RPM2024I2LCD-L20P (-HW/-L20P)
Input						
On/Off Switch	No	No	No	No	No	No
Power On/Off LED	No	No	Yes	Yes	Yes	Yes
Input Voltage	200V-240V	200V-240V	200V-240V	200V-240V	200V-240V	200V-240V
Input Plug (Cord Length)	IEC C20 (8-feet)	NEMA L6-20P (10-ft)	Hardwire (10-ft) NEMA L6-20P (10-ft)	Hardwire (10-ft) NEMA L6-20P (10-ft)	Hardwire (10-ft) NEMA L6-20P (10-ft)	Hardwire (10-ft) NEMA L6-20P (10-ft)
Input Protection	Yes	Yes	Yes	Yes	Yes	Yes
Hydraulic-Magnetic Breakers	Yes	Yes	No	No	No	No
Max Input Current (A)	20 Amps	20 Amps	20 Amps	20 Amps	20 Amps	20 Amps
Surge-protection Joule Rating	N/A	N/A	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A	N/A	N/A
Earth-ground Lug	No	Yes	Yes	Yes	Yes	Yes
Output						
Output Voltage	200V-240V	200V-240V	200V-240V	200V-240V	200V-240V	200V-240V
Maximum Output Rating (A)	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps
Number of Output Circuits	N/A	No	One	One	One	One
Front Panel Receptacles (Qty)	(8) IEC320 C13	(7) IEC320 C13, (1) IEC320 C19	N/A	N/A	(14) IEC320 C13, (2) IEC320 C19	(21) IEC320 C13, (3) IEC320 C19
Rear Panel Receptacles (Qty)	N/A	N/A	(4) IEC320 C13	(8) IEC320 C13	N/A	N/A
Management						
Web & SNMP Management	Yes	Yes	Yes	Yes	Yes	Yes
10/100/1000 Mbit Compatible	10/100	10/100	10/100	10/100	10/100	10/100
Network port Sharing	No	Yes	Yes	Yes	Yes	Yes
Individual Outlet Control	Yes	Yes	Yes	Yes	Yes	Yes
Individual Outlet Metering	No	No	No	No	No	No
Combined Outlet Metering	Yes	Yes	Yes	Yes	Yes	Yes
Multi-level User Access	Yes	Yes	Yes	Yes	Yes	Yes
On/Off Outlet Sequencing	Yes	Yes	Yes	Yes	Yes	Yes
On/Off Outlet Scheduling	Yes	Yes	Yes	Yes	Yes	Yes
Event Configuration	Yes	Yes	Yes	Yes	Yes	Yes
Outlet Grouping	Yes	Yes	Yes	Yes	Yes	Yes
Auto Ping Function	N/A	N/A	Yes	Yes	Yes	Yes
SNMP IPv4/IPv6 Compatible	Yes	Yes	Yes	Yes	Yes	Yes
SNMPv3 Compatible	N/A	N/A	Yes	Yes	Yes	Yes
SSH/SSL Compatible	Yes	Yes	Yes	Yes	Yes	Yes
TLS v1.2 or Greater	Yes	N/A	Yes	Yes	Yes	Yes
Env. Sensor Compatible	No	Yes	Yes	Yes	Yes	Yes
Flash Firmware Upgrades	No	Yes	Yes	Yes	Yes	Yes
Remote Batch Updates	No	N/A	N/A	N/A	N/A	N/A
Physical						
All-metal case	N/A	N/A	Yes	Yes	Yes	Yes
Installation Format (H/V)	Horizontal (1U)	Vertical (0U)	Horizontal (1U), Vertical (0U)	Horizontal (1U), Vertical (0U)	Vertical (0U)	Vertical (0U)
Color-coded Receptacles	No	No	No	No	No	No
Dimensions (HxWxD)	1.73" x 17.5" x 4.25"	39" x 2.2" x 1.8"	1.75" x 17.0" x 8.5"	1.75" x 17.01" x 8.50"	49.00" x 2.20" x 3.54"	74.41" x 2.20" x 4.33"
Weight	5 lbs.	8.7 lbs.	8.82 lbs.	8.82 lbs.	8.82 lbs.	13.32 lbs.
Warranty & Certifications						
62368-1 Certification	No	No	Yes	Yes	Yes	Yes
RoHS Compliant	Yes	Yes	Yes	Yes	Yes	Yes
TAA Compliant	No	No	Yes	Yes	Yes	Yes
Warranty	2 Years	2 Years	3 Years	3 Years	3 Years	3 Years

All names and trademarks are the property of the respective companies.

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

(Competitor) Advantage in **BOLD**)

(MM Advantage in **BOLD**)

Feature Comparison Chart of MM RPM Series vs. APC AP Series*

FEATURES	AP Series		Minuteman RPM Series		
	AP7911B	APDU9941/US	RPM308I2LCD (-HW/-L30P)	RPM3016I2LCD-HW (-HW/-L30P)	RPM3024I2LCD-HW (-HW/-L30P)
Input					
On/Off Switch	No	No	No	No	No
Power On/Off LED	No	Yes	Yes	Yes	Yes
Input Voltage	200V-240V	200V-240V	200V-240V	200V-240V	200V-240V
Input Plug (Cord Length)	NEMA L6-30P (12-ft)	L6-30P (10-ft)	Hardwire (10-ft) NEMA L6-30P (10-ft)	Hardwire (10-ft) NEMA L6-30P (10-ft)	Hardwire (10-ft) NEMA L6-30P (10-ft)
Input Protection	Yes, (2) 20 Amp Breaker	Yes, (2) 20 Amp Breaker	Yes	Yes	Yes
Hydraulic-Magnetic Breakers	Yes	Yes	No	No	No
Max Input Current (A)	30 Amps	30 Amps	30 Amps	30 Amps	30 Amps
Surge-protection Joule Rating	N/A	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A	N/A
Earth-ground Lug	Yes	Yes	Yes	Yes	Yes
Output					
Output Voltage	200V-240V	200V-240V	200V-240V	200V-240V	200V-240V
Maximum Output Rating (A)	24 Amps	24 Amps	24 Amps	24 Amps	24 Amps
Number of Output Circuits	N/A	N/A	One	One	One
Front Panel Receptacles (Qty)	(16) IEC320 C13	(21) IEC320 C13/C15, (3) IEC320 C19/C21	N/A	(14) IEC320 C13, (2) IEC320 C19	(21) IEC320 C13, (3) IEC320 C19
Rear Panel Receptacles (Qty)	N/A	N/A	(8) IEC320 C13	N/A	N/A
Management					
Web & SNMP Management	Yes	Yes	Yes	Yes	Yes
10/100/1000 Mbit Compatible	10/100	Yes	10/100	10/100	10/100
Network port Sharing	No	Yes	Yes	Yes	Yes
Individual Outlet Control	Yes	Yes	Yes	Yes	Yes
Individual Outlet Metering	No	Yes	No	No	No
Combined Outlet Metering	Yes	No	Yes	Yes	Yes
Multi-level User Access	Yes	Yes	Yes	Yes	Yes
On/Off Outlet Sequencing	Yes	Yes	Yes	Yes	Yes
On/Off Outlet Scheduling	Yes	Yes	Yes	Yes	Yes
Event Configuration	Yes	Yes	Yes	Yes	Yes
Outlet Grouping	Yes	Yes	Yes	Yes	Yes
Auto Ping Function	N/A	Yes	Yes	Yes	Yes
SNMP IPv4/IPv6 Compatible	Yes	Yes	Yes	Yes	Yes
SNMPv3 Compatible	N/A	Yes	Yes	Yes	Yes
SSH/SSL Compatible	Yes	Yes	Yes	Yes	Yes
TLS v1.2 or Greater	Yes	Yes	Yes	Yes	Yes
Env. Sensor Compatible	No	Yes	Yes	Yes	Yes
Flash Firmware Upgrades	No	Yes	Yes	Yes	Yes
Remote Batch Updates	No	Yes	N/A	N/A	N/A
Physical					
All-metal case	N/A	N/A	Yes	Yes	Yes
Installation Format (H/V)	Horizontal (2U)	Vertical (0)	Horizontal (1U), Vertical (0U)	Vertical (0U)	Vertical (0U)
Color-coded Receptacles	No	No	No	No	No
Dimensions (HxWxD) Inches	3.5" x 17.5" x 4.5"	72.01" x 2.18" x 1.82"	1.75" x 17.01" x 8.50"	49.02" x 2.20" x 3.15"	70.00" x 2.20" x 3.54"
Weight	9.9 lbs.	18.75 lbs.	9.70 lbs.	12.78 lbs.	17.63 lbs.
Warranty & Certifications					
62368-1 Certification	No	Yes	Yes	Yes	Yes
RoHS Compliant	Yes	Yes	Yes	Yes	Yes
TAA Compliant	No	No/Yes	Yes	Yes	Yes
Warranty	2 Years	3 Years	3 Years	3 Years	3 Years

All names and trademarks are the property of the respective companies.

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

(Competitor) Advantage in **BOLD**

(MM Advantage in **BOLD**)

Feature Comparison Chart of MM RPM Series vs. CyberPower Series*

FEATURES	PDU Series					Minuteman RPM Series				
	PDU41001	PDU41021	PDU15SW (8FNET)	PDU41116	PDU15SWV16FNET	RPM1521E	RPM1581HVN	RPM158N1CD-HW (-15P /-IEC)	RPM1516N1CD-HW (15P /-IEC)	RPM1524N1CD-HW (-15P /-IEC)
Input										
On/Off Switch	No	No	No	No	No	Yes	No	No	No	No
Power On/Off LED	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Input Voltage	100V-120V	100V-120V	100V-120V	100V-120V	100V-120V	120V	100V-120V	100V-127V	100V-127V	100V-127V
Input Plug (Cord Length)	NEMA 5-15P (12-ft)	NEMA 5-15P (12-ft)	NEMA 5-15P (12-ft)	NEMA 5-15P (10-ft)	NEMA 5-15P (10-ft)	NEMA 5-15P (6-ft)	NEMA 5-15P (10-ft)	Hardwire (10-ft) NEMA 5-15P (10-ft) IEC C20 (10-ft)	Hardwire (10-ft) NEMA 5-15P (10-ft) IEC C20 (10-ft)	Hardwire (10-ft) NEMA 5-15P (10-ft) IEC C20 (10-ft)
Input Protection	Yes	Yes	No	Yes	No	Yes	Yes	Yes	Yes	Yes
Hydraulic-Magnetic Breakers	N/A	N/A	N/A	N/A	N/A	No	No	No	No	No
Max Input Current (A)	15 Amps	15 Amps	15 Amps	15 Amps	15 Amps	15 Amps	15 Amps	15 Amps	15 Amps	15 Amps
Surge-protection Joule Rating	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Earth-ground Lug	Yes	Yes	No	Yes	No	No	No	Yes	Yes	Yes
Output										
Output Voltage	100V-120V	100V-120V	100V-120V	100V-120V	100V-120V	120V	100V-120V	100V-127V	100V-127V	100V-127V
Maximum Output Rating (A)	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps
Number of Output Circuits	N/A	N/A	N/A	N/A	N/A	N/A	N/A	One	One	One
Front Panel Receptacles (Qty)	(8) NEMA 5-15R	(8) NEMA 5-15R	(8) NEMA 5-15R	(16) NEMA 5-15R	(16) NEMA 5-15R	N/A	(8) NEMA 5-15R	N/A	N/A	N/A
Rear Panel Receptacles (Qty)	N/A	(8) NEMA 5-15R	N/A	N/A	N/A	(2) NEMA 5-15R	N/A	(8) NEMA 5-15R	(16) NEMA 5-15R	(24) NEMA 5-15R
Management										
Web & SNMP Management	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
10/100/1000 Mbit Compatible	N/A	N/A	N/A	N/A	N/A	N/A	N/A	10/100	10/100	10/100
Network port Sharing	Yes	Yes	No	Yes	No	Yes	Yes	Yes	Yes	Yes
Individual Outlet Control	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Individual Outlet Metering	Yes	Yes	Yes	Yes	Yes	No	No	No	No	No
Combined Outlet Metering	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Multi-level User Access	N/A	N/A	No	N/A	No	Yes	Yes	Yes	Yes	Yes
On/Off Outlet Sequencing	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
On/Off Outlet Scheduling	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Event Configuration	Yes	Yes	N/A	Yes	N/A	Yes	Yes	Yes	Yes	Yes
Outlet Grouping	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Auto Ping Function	No	No	No	No	No	Yes	Yes	Yes	Yes	Yes
SNMP IPv4/IPv6 Compatible	Yes	Yes	No	Yes	No	No	No	Yes	Yes	Yes
SNMPv3 Compatible	Yes	Yes	N/A	Yes	N/A	Yes	Yes	Yes	Yes	Yes
SSH/SSL Compatible	Yes	Yes	No	Yes	No	Yes	Yes	Yes	Yes	Yes
TLS v1.2 or Greater	N/A	N/A	No	N/A	No	Yes	Yes	Yes	Yes	Yes
Env. Sensor Compatible	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Flash Firmware Upgrades	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Remote Batch Updates	Yes	Yes	No	Yes	No	N/A	N/A	N/A	N/A	N/A
Physical										
All-metal case	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Installation Format (H/V)	Horizontal, Vertical, Under-counter, Wallmount (0U, 1U)	Horizontal, Vertical, Under-counter, Wallmount (0U, 1U)	Horizontal, Vertical, Under-counter, Wallmount (0U, 1U)	Vertical, Under-counter, Wallmount (0U)	Vertical (0U), Under-counter, Wallmount	Horizontal	Horizontal (1U), Vertical (0U)	Horizontal (1U), Vertical (0U)	Vertical (0U)	Vertical (0U)
Color-coded Receptacles	No	No	No	No	No	No	No	No	No	No
Dimensions (HxWxD)	1.75" x 17.05" x 4.41" (1U Installation)	1.75" x 17.05" x 8.45" (1U Installation)	1.75" x 17.05" x 4.41" (1U Installation)	53.1" x 1.9" x 2.2"	49" x 2.2" x 1.75"	1.7" x 4.9" x 7.17"	1.73" x 17" x 3.54"	1.75" x 5.83" x 17.01"	49.02" x 2.20" x 3.07"	70.00" x 2.20" x 3.07"
Weight	5.7 lbs.	8.4 lbs.	5.29 lbs.	11.9 lbs.	9 lbs.	1.78 lbs.	4.85 lbs.	7.72 lbs.	8.82 lbs.	13.22 lbs.
Warranty & Certifications										
62368-1 Certification	Yes	Yes	No	Yes	No	No	Yes	Yes	Yes	Yes
RoHS Compliant	Yes	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes
TAA Compliant	No	No	No	No	No	Yes	Yes	Yes	Yes	Yes
Warranty	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years

All names and trademarks are the property of the respective companies.

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

(Competitor) Advantage in **BOLD**

(MM Advantage in **BOLD**)

Feature Comparison Chart of MM RPM Series vs. CyberPower Series*

FEATURES	PDU Series			Minuteman RPM Series		
	PDU41002	PDU20SWT (8FNET)	PDU41101	RPM208N1LCD-HW (-20P/-L20P/-IEC)	RPM2016N1LCD-HW (-20P/-L20P/-IEC)	RPM2024N1LCD-HW (-20P/-L20P/-IEC)
Input						
On/Off Switch	No	No	No	No	No	No
Power On/Off LED	Yes	Yes	Yes	Yes	Yes	Yes
Input Voltage	100V-120V	100V-120V	100V-120V	100V-127V	100V-127V	100V-127V
Input Plug (Cord Length)	NEMA L5-20P (12-ft)/ w/5-20P Adaptor	NEMA 5-20P / L5-20P (12-ft)	NEMA L5-20P (10-ft)/ w/5-20P Adaptor	Hardwire (10-ft) NEMA 5-20P (10-ft) NEMA L5-20P (10-ft) IEC320 C20 (10-ft)	Hardwire (10-ft) NEMA 5-20P (10-ft) NEMA L5-20P (10-ft) IEC320 C20 (10-ft)	Hardwire (10-ft) NEMA 5-20P (10-ft) NEMA L5-20P (10-ft) IEC320 C20 (10-ft)
Input Protection	No	No	No	Yes	Yes	Yes
Hydraulic-Magnetic Breakers	N/A	N/A	N/A	No	No	No
Max Input Current (A)	20 Amps	20 Amps	20 Amps	20 Amps	20 Amps	20 Amps
Surge-protection Joule Rating	N/A	N/A	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A	N/A	N/A
Earth-ground Lug	Yes	Yes	No	Yes	Yes	Yes
Output						
Output Voltage	100V-120V	100V-120V	100V-120V	100V-127V	100V-127V	100V-127V
Maximum Output Rating (A)	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps
Number of Output Circuits	N/A	N/A	N/A	One	One	One
Front Panel Receptacles (Qty)	(8) NEMA 5-20R	(8) NEMA 5-20R	(24) NEMA 5-20R	N/A	(16) NEMA 5-15/20R	(24) NEMA 5-15/20R
Rear Panel Receptacles (Qty)	N/A	N/A	N/A	(8) NEMA 5-15/20R	N/A	N/A
Management						
Web & SNMP Management	Yes	Yes	Yes	Yes	Yes	Yes
10/100/1000 Mbit Compatible	N/A	N/A	N/A	10/100	10/100	10/100
Network port Sharing	Yes	No	Yes	Yes	Yes	Yes
Individual Outlet Control	Yes	Yes	Yes	Yes	Yes	Yes
Individual Outlet Metering	Yes	Yes	Yes	No	No	No
Combined Outlet Metering	Yes	Yes	Yes	Yes	Yes	Yes
Multi-level User Access	N/A	No	N/A	Yes	Yes	Yes
On/Off Outlet Sequencing	Yes	Yes	Yes	Yes	Yes	Yes
On/Off Outlet Scheduling	Yes	Yes	Yes	Yes	Yes	Yes
Event Configuration	Yes	N/A	Yes	Yes	Yes	Yes
Outlet Grouping	Yes	Yes	Yes	Yes	Yes	Yes
Auto Ping Function	No	No	No	Yes	Yes	Yes
SNMP IPv4/IPv6 Compatible	Yes	No	Yes	Yes	Yes	Yes
SNMPv3 Compatible	Yes	N/A	Yes	Yes	Yes	Yes
SSH/SSL Compatible	Yes	No	Yes	Yes	Yes	Yes
TLS v1.2 or Greater	N/A	No	N/A	Yes	Yes	Yes
Env. Sensor Compatible	Yes	Yes	Yes	Yes	Yes	Yes
Flash Firmware Upgrades	Yes	Yes	Yes	Yes	Yes	Yes
Remote Batch Updates	Yes	No	Yes	N/A	N/A	N/A
Physical						
All-metal case	Yes	Yes	Yes	Yes	Yes	Yes
Installation Format (H/V)	Horizontal, Vertical, Under-counter, Wallmount (0U, 1U)	Horizontal, Vertical, Under-counter, Wallmount (0U, 1U)	Vertical (0U), Under-counter, Wallmount	Horizontal (1U), Vertical (0U)	Vertical (0U)	Vertical (0U)
Color-coded Receptacles	No	No	No	No	No	No
Dimensions (HxWxD)	1.75" x 17.05 x 4.41" (1U Installation)	1.75" x 17.05 x 4.41" (1U Installation)	65.5" x 2.2" x 1.9" (0U Installation)	1.75" x 17.01" x 5.83"	49.02" x 2.20" x 3.07"	70.00" x 2.20" x 3.07"
Weight	7.3 lbs.	6.17 lbs.	15.43 lbs.	7.72 lbs.	8.82 lbs.	13.22 lbs.
Warranty & Certifications						
62368-1 Certification	Yes	No	Yes	Yes	Yes	Yes
RoHS Compliant	Yes	Yes	No	Yes	Yes	Yes
TAA Compliant	No	No	No	Yes	Yes	Yes
Warranty	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years

All names and trademarks are the property of the respective companies.

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

(Competitor) Advantage in **BOLD**

(MM Advantage in **BOLD**)

Feature Comparison Chart of MM RPM Series vs. CyberPower Series*

FEATURES	PDU Series			Minuteman RPM Series		
	PDU41023	PDU41003	PDU41102	RPM308N1LCD-HW (-L30P)	RPM3016N1LCD-HW (-L30P)	RPM3024N1LCD -HW (-L30P)
Input						
On/Off Switch	No	No	No	No	No	No
Power On/Off LED	Yes	Yes	Yes	Yes	Yes	Yes
Input Voltage	100V-120V	100V-120V	100V-120V	100V-127V	100V-127V	100V-127V
Input Plug (Cord Length)	NEMA L5-30P (12-ft)	NEMA L5-30P (12-ft)	NEMA L5-30P (10-ft)	Hardwire (10-ft) NEMA L6-30P (10-ft)	Hardwire (10-ft) NEMA L6-30P (10-ft)	Hardwire (10-ft) NEMA L6-30P (10-ft)
Input Protection	Yes, (2) 20 Amp	Yes, (2) 20 Amp	Yes, (2) 20 Amp	Yes	Yes	Yes
Hydraulic-Magnetic Breakers	No	No	No	No	No	No
Max Input Current (A)	30 Amps	30 Amps	30 Amps	30 Amps	30 Amps	30 Amps
Surge-protection Joule Rating	N/A	N/A	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A	N/A	N/A
Earth-ground Lug	Yes	Yes	No	Yes	Yes	Yes
Output						
Output Voltage	100V-120V	100V-120V	100V-120V	100V-127V	100V-127V	100V-127V
Maximum Output Rating (A)	24 Amps	24 Amps	24 Amps	24 Amps	24 Amps	24 Amps
Number of Output Circuits	N/A	N/A	N/A	One	One	One
Front Panel Receptacles (Qty)	(8) NEMA 5-20R	(16) NEMA 5-20R	(24) NEMA 5-20R	N/A	(16) NEMA 5-15/20R	(24) NEMA 5-15/20R
Rear Panel Receptacles (Qty)	(8) NEMA 5-20R	N/A	N/A	(8) NEMA 5-15/20R	N/A	N/A
Management						
Web & SNMP Management	Yes	Yes	Yes	Yes	Yes	Yes
10/100/1000 Mbit Compatible	N/A	N/A	N/A	10/100	10/100	10/100
Network port Sharing	Yes	Yes	Yes	Yes	Yes	Yes
Individual Outlet Control	Yes	Yes	Yes	Yes	Yes	Yes
Individual Outlet Metering	No	Yes	Yes	No	No	No
Combined Outlet Metering	Yes	Yes	Yes	Yes	Yes	Yes
Multi-level User Access	N/A	N/A	N/A	Yes	Yes	Yes
On/Off Outlet Sequencing	Yes	Yes	Yes	Yes	Yes	Yes
On/Off Outlet Scheduling	Yes	Yes	Yes	Yes	Yes	Yes
Event Configuration	Yes	Yes	Yes	Yes	Yes	Yes
Outlet Grouping	Yes	Yes	Yes	Yes	Yes	Yes
Auto Ping Function	No	No	No	Yes	Yes	Yes
SNMP IPv4/IPv6 Compatible	Yes	Yes	Yes	Yes	Yes	Yes
SNMPv3 Compatible	Yes	Yes	Yes	Yes	Yes	Yes
SSH/SSL Compatible	Yes	Yes	Yes	Yes	Yes	Yes
TLS v1.2 or Greater	N/A	N/A	N/A	Yes	Yes	Yes
Env. Sensor Compatible	Yes	Yes	Yes	Yes	Yes	Yes
Flash Firmware Upgrades	Yes	Yes	Yes	Yes	Yes	Yes
Remote Batch Updates	Yes	Yes	Yes	N/A	N/A	N/A
Physical						
All-metal case	Yes	Yes	Yes	Yes	Yes	Yes
Installation Format (H/V)	Horizontal, Vertical, Under-counter, Wallmount (0U, 1U)	Horizontal (2U), Wallmount	Vertical (0U), Under-counter, Wallmount	Horizontal/1U, Vertical/0U	Vertical (0U)	Vertical (0U)
Color-coded Receptacles	No	No	No	No	No	No
Dimensions (HxWxD)	1.75" x 17.05" x 8.45"	3.5" x 17.05" x 4.41"	65.5" x 2.2" x 1.9"	1.76" x 17.00" x 8.50"	49.02" x 2.20" x 3.54"	70.00" x 2.20" x 3.54"
Weight	9.9 lbs.	7.3 lbs.	17.2 lbs.	8.22 lbs.	9.26 lbs.	17.63 lbs.
Warranty & Certifications						
62368-1 Certification	Yes	Yes	Yes	Yes	Yes	Yes
RoHS Compliant	Yes	Yes	Yes	Yes	Yes	Yes
TAA Compliant	No	No	No	Yes	Yes	Yes
Warranty	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years

and trademarks are the property of the respective companies.

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

(Competitor) Advantage in **BOLD**

(MM Advantage in **BOLD**)

Feature Comparison Chart of MM RPM Series vs. CyberPower Series*

FEATURES	PDU Series	Minuteman RPM Series			
	PDU41104	RPM204I2LCD (-HW/-L20P)	RPM208I2LCD-L20P (-HW/-L20P)	RPM2016I2LCD-L20P (-HW/-L20P)	RPM2024I2LCD-L20P (-HW/-L20P)
Input					
On/Off Switch	No	No	No	No	No
Power On/Off LED	Yes	Yes	Yes	Yes	Yes
Input Voltage	200V-240V	200V-240V	200V-240V	200V-240V	200V-240V
Input Plug (Cord Length)	NEMA L6-20P (10-ft)	Hardwire (10-ft) NEMA L6-20P (10-ft)	Hardwire (10-ft) NEMA L6-20P (10-ft)	Hardwire (10-ft) NEMA L6-20P (10-ft)	Hardwire (10-ft) NEMA L6-20P (10-ft)
Input Protection	No	Yes	Yes	Yes	Yes
Hydraulic-Magnetic Breakers	N/A	No	No	No	No
Max Input Current (A)	20 Amps	20 Amps	20 Amps	20 Amps	20 Amps
Surge-protection Joule Rating	N/A	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A	N/A
Earth-ground Lug	No	Yes	Yes	Yes	Yes
Output					
Output Voltage	200V-240V	200V-240V	200V-240V	200V-240V	200V-240V
Maximum Output Rating (A)	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps
Number of Output Circuits	N/A	One	One	One	One
Front Panel Receptacles (Qty)	(21) IEC320 C13, (3) IEC320 C19	N/A	N/A	(14) IEC320 C13, (2) IEC320 C19	(21) IEC320 C13, (3) IEC320 C19
Rear Panel Receptacles (Qty)	N/A	(4) IEC320 C13	(8) IEC320 C13	N/A	N/A
Management					
Web & SNMP Management	Yes	Yes	Yes	Yes	Yes
10/100/1000 Mbit Compatible	N/A	10/100	10/100	10/100	10/100
Network port Sharing	Yes	Yes	Yes	Yes	Yes
Individual Outlet Control	Yes	Yes	Yes	Yes	Yes
Individual Outlet Metering	Yes	No	No	No	No
Combined Outlet Metering	Yes	Yes	Yes	Yes	Yes
Multi-level User Access	N/A	Yes	Yes	Yes	Yes
On/Off Outlet Sequencing	Yes	Yes	Yes	Yes	Yes
On/Off Outlet Scheduling	Yes	Yes	Yes	Yes	Yes
Event Configuration	Yes	Yes	Yes	Yes	Yes
Outlet Grouping	Yes	Yes	Yes	Yes	Yes
Auto Ping Function	No	Yes	Yes	Yes	Yes
SNMP IPv4/IPv6 Compatible	Yes	Yes	Yes	Yes	Yes
SNMPv3 Compatible	Yes	Yes	Yes	Yes	Yes
SSH/SSL Compatible	Yes	Yes	Yes	Yes	Yes
TLS v1.2 or Greater	N/A	Yes	Yes	Yes	Yes
Env. Sensor Compatible	Yes	Yes	Yes	Yes	Yes
Flash Firmware Upgrades	Yes	Yes	Yes	Yes	Yes
Remote Batch Updates	Yes	N/A	N/A	N/A	N/A
Physical					
All-metal case	Yes	Yes	Yes	Yes	Yes
Installation Format (H/V)	Vertical (0U), Under-counter, Wallmount	Horizontal (1U), Vertical (0U)	Horizontal (1U), Vertical (0U)	Vertical (0U)	Vertical (0U)
Color-coded Receptacles	No	No	No	No	No
Dimensions (HxWxD)	65.5" x 2.2" x 1.9"	1.75" x 17.0" x 8.5"	1.75" x 17.01" x 8.50"	49.00" x 2.20" x 3.54"	74.41" x 2.20" x 4.33"
Weight	17.2 lbs.	8.82 lbs.	8.82 lbs.	8.82 lbs.	13.32 lbs.
Warranty & Certifications					
62368-1 Certification	Yes	Yes	Yes	Yes	Yes
RoHS Compliant	Yes	Yes	Yes	Yes	Yes
TAA Compliant	No	Yes	Yes	Yes	Yes
Warranty	3 Years	3 Years	3 Years	3 Years	3 Years

All names and trademarks are the property of the respective companies.

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

(Competitor) Advantage in **BOLD**

(MM Advantage in **BOLD**)

Feature Comparison Chart of MM RPM Series vs. CyberPower Series*

FEATURES	PDU Series				Minuteman RPM Series		
	PDU41008	PDU30SWHVT16FNET	PDU41105	PDU30SWHVT24FNET	RPM30812LCD (-HW/-L30P)	RPM301612LCD-HW (-HW/-L30P)	RPM302412LCD-HW (-HW/-L30P)
Input							
On/Off Switch	No	No	No	No	No	No	No
Power On/Off LED	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Input Voltage	200V-240V	200V-240V	200V-240V	200V-240V	200V-240V	200V-240V	200V-240V
Input Plug (Cord Length)	NEMA L6-30P (12-ft)	NEMA L6-30P (10-ft)	NEMA L6-30P (10-ft)	NEMA L6-30P (10-ft)	Hardwire (10-ft) NEMA L6-30P (10-ft)	Hardwire (10-ft) NEMA L6-30P (10-ft)	Hardwire (10-ft) NEMA L6-30P (10-ft)
Input Protection	Yes, (2) 20 Amp	Yes, (2) 20 Amp	Yes, (2) 20 Amp	Yes, (2) 15 Amp	Yes	Yes	Yes
Hydraulic-Magnetic Breakers	No	No	No	No	No	No	No
Max Input Current (A)	30 Amps	30 Amps	30 Amps	30 Amps	30 Amps	30 Amps	30 Amps
Surge-protection Joule Rating	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Earth-ground Lug	Yes	Yes	No	No	Yes	Yes	Yes
Output							
Output Voltage	200V-240V	200V-240V	200V-240V	200V-240V	200V-240V	200V-240V	200V-240V
Maximum Output Rating (A)	24 Amps	24 Amps	24 Amps	24 Amps	24 Amps	24 Amps	24 Amps
Number of Output Circuits	N/A	N/A	N/A	N/A	One	One	One
Front Panel Receptacles (Qty)	(12) IEC320 C13, IEC320 C19	(16) IEC320 C13	(21) IEC320 C13, (3) IEC320 C19	(21) IEC320 C13, (3) IEC320 C19	N/A	(14) IEC320 C13, (2) IEC320 C19	(21) IEC320 C13, (3) IEC320 C19
Rear Panel Receptacles (Qty)	N/A	N/A	N/A	N/A	(8) IEC320 C13	N/A	N/A
Management							
Web & SNMP Management	Yes	Yes	Yes	Yes	Yes	Yes	Yes
10/100/1000 Mbit Compatible	N/A	N/A	N/A	N/A	10/100	10/100	10/100
Network port Sharing	Yes	No	Yes	No	Yes	Yes	Yes
Individual Outlet Control	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Individual Outlet Metering	Yes	Yes	Yes	Yes	No	No	No
Combined Outlet Metering	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Multi-level User Access	N/A	No	N/A	No	Yes	Yes	Yes
On/Off Outlet Sequencing	Yes	Yes	Yes	Yes	Yes	Yes	Yes
On/Off Outlet Scheduling	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Event Configuration	Yes	N/A	Yes	N/A	Yes	Yes	Yes
Outlet Grouping	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Auto Ping Function	No	No	No	No	Yes	Yes	Yes
SNMP IPv4/IPv6 Compatible	Yes	IPv4	Yes	IPv4	Yes	Yes	Yes
SNMPv3 Compatible	Yes	N/A	Yes	N/A	Yes	Yes	Yes
SSH/SSL Compatible	Yes	No	Yes	No	Yes	Yes	Yes
TLS v1.2 or Greater	N/A	No	N/A	No	Yes	Yes	Yes
Env. Sensor Compatible	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Flash Firmware Upgrades	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Remote Batch Updates	Yes	No	Yes	No	N/A	N/A	N/A
Physical							
All-metal case	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Installation Format (H/V)	Horizontal (2U), Wallmount	Horizontal (2U), Wallmount	Vertical (0U), Under-counter, Wallmount	Vertical (0U), Under-counter, Wallmount	Horizontal (1U), Vertical (0U)	Vertical (0U)	Vertical (0U)
Color-coded Receptacles	No	No	No	No	No	No	No
Dimensions (HxWxD)	3.5" x 17.05" x 4.41"	3.5" x 17.05" x 4.41"	65.5" x 2.2" x 1.9"	70" x 2.2" x 1.75"	1.75" x 17.01" x 8.50"	49.02" x 2.20" x 3.15"	70.00" x 2.20" x 3.54"
Weight	9.9 lbs.	9.04 lbs.	17.64 lbs.	15.2 lbs.	9.70 lbs.	12.78 lbs.	17.63 lbs.
Warranty & Certifications							
62368-1 Certification	Yes	No	Yes	No	Yes	Yes	Yes
RoHS Compliant	Yes	Yes	No	Yes	Yes	Yes	Yes
TAA Compliant	No	No	No	No	Yes	Yes	Yes
Warranty	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years

All names and trademarks are the property of the respective companies.

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

(Competitor) Advantage in **BOLD**

(MM Advantage in **BOLD**)

Feature Comparison Chart of MM RPM Series vs. Vertiv rPDU Series*

FEATURES	rPDU Series	Minuteman RPM Series				
	VP5N11A0	RPM1521E	RPM1581HVN	RPM158N1LCD-HW (-15P /-IEC)	RPM1516N1LCD-HW (15P /-IEC)	RPM1524N1LCD-HW (-15P /-IEC)
Input						
On/Off Switch	N/A	Yes	No	No	No	No
Power On/Off LED	N/A	Yes	Yes	Yes	Yes	Yes
Input Voltage	120V	120V	100V-120V	100V-127V	100V-127V	100V-127V
Input Plug (Cord Length)	NEMA 5-15P	NEMA 5-15P (6-ft)	NEMA 5-15P (10-ft)	Hardwire (10-ft) NEMA 5-15P (10-ft) IEC C20 (10-ft)	Hardwire (10-ft) NEMA 5-15P (10-ft) IEC C20 (10-ft)	Hardwire (10-ft) NEMA 5-15P (10-ft) IEC C20 (10-ft)
Input Protection	N/A	Yes	Yes	Yes	Yes	Yes
Hydraulic-Magnetic Breakers	N/A	No	No	No	No	No
Max Input Current (A)	N/A	15 Amps	15 Amps	15 Amps	15 Amps	15 Amps
Surge-protection Joule Rating	N/A	N/A	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A	N/A	N/A
Earth-ground Lug	N/A	No	No	Yes	Yes	Yes
Output						
Output Voltage	120V	120V	100V-120V	100V-127V	100V-127V	100V-127V
Maximum Output Rating (A)	N/A	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps
Number of Output Circuits	N/A	N/A	One	One	One	One
Front Panel Receptacles (Qty)	(6) NEMA 5-15R	N/A	(8) NEMA 5-15R	N/A	N/A	N/A
Rear Panel Receptacles (Qty)	N/A	(2) NEMA 5-15R	N/A	(8) NEMA 5-15R	(16) NEMA 5-15R	(24) NEMA 5-15R
Management						
Web & SNMP Management	Yes	Yes	Yes	Yes	Yes	Yes
10/100/1000 Mbit Compatible	Yes	N/A	N/A	10/100	10/100	10/100
Network port Sharing	Yes	Yes	Yes	Yes	Yes	Yes
Individual Outlet Control	Yes	Yes	Yes	Yes	Yes	Yes
Individual Outlet Metering	No	No	No	No	No	No
Combined Outlet Metering	Yes	Yes	Yes	Yes	Yes	Yes
Multi-level User Access	N/A	Yes	Yes	Yes	Yes	Yes
On/Off Outlet Sequencing	Yes	Yes	Yes	Yes	Yes	Yes
On/Off Outlet Scheduling	N/A	Yes	Yes	Yes	Yes	Yes
Event Configuration	N/A	Yes	Yes	Yes	Yes	Yes
Outlet Grouping	Yes	Yes	Yes	Yes	Yes	Yes
Auto Ping Function	N/A	Yes	Yes	Yes	Yes	Yes
SNMP IPv4/IPv6 Compatible	N/A	No	No	Yes	Yes	Yes
SNMPv3 Compatible	N/A	Yes	Yes	Yes	Yes	Yes
SSH/SSL Compatible	N/A	Yes	Yes	Yes	Yes	Yes
TLS v1.2 or Greater	N/A	Yes	Yes	Yes	Yes	Yes
Env. Sensor Compatible	Yes	Yes	Yes	Yes	Yes	Yes
Flash Firmware Upgrades	N/A	Yes	Yes	Yes	Yes	Yes
Remote Batch Updates	N/A	N/A	N/A	N/A	N/A	N/A
Physical						
All-metal case	N/A	Yes	Yes	Yes	Yes	Yes
Installation Format (H/V)	Horizontal	Horizontal	Horizontal (1U), Vertical (0U)	Horizontal (1U), Vertical (0U)	Vertical (0U)	Vertical (0U)
Color-coded Receptacles	Yes	No	No	No	No	No
Dimensions (HxWxD)	1.72" x 17" x 12"	1.7" x 4.9" x 7.17"	1.73" x 17" x 3.54"	1.75" x 5.83" x 17.01"	49.02" x 2.20" x 3.07"	70.00" x 2.20" x 3.07"
Weight	10 lbs.	1.78 lbs.	4.85 lbs.	7.72 lbs.	8.82 lbs.	13.22 lbs.
Warranty & Certifications						
62368-1 Certification	No	No	Yes	Yes	Yes	Yes
RoHS Compliant	Yes	Yes	No	Yes	Yes	Yes
TAA Compliant	Yes	Yes	Yes	Yes	Yes	Yes
Warranty	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years

All names and trademarks are the property of the respective companies.

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

(Competitor) Advantage in **BOLD**

(MM Advantage in **BOLD**)

Feature Comparison Chart of MM RPM Series vs. Vertiv rPDU Series*

FEATURES	rPDU Series			Minuteman RPM Series		
	VP5N21A1	VP5N31A0	VP5N30A4	RPM208N1LCD-HW (-20P /-L20P /-IEC)	RPM2016N1LCD-HW (-20P/-L20P/-IEC)	RPM2024N1LCD-HW (-20P/-L20P/-IEC)
Input						
On/Off Switch	N/A	N/A	N/A	No	No	No
Power On/Off LED	N/A	N/A	N/A	Yes	Yes	Yes
Input Voltage	120V	120V	120V	100V-127V	100V-127V	100V-127V
Input Plug (Cord Length)	NEMA L5-20P	NEMA L5-20P	NEMA L5-20P	Hardwire (10-ft) NEMA 5-20P (10-ft) NEMA L5-20P (10-ft) IEC320 C20 (10-ft)	Hardwire (10-ft) NEMA 5-20P (10-ft) NEMA L5-20P (10-ft) IEC320 C20 (10-ft)	Hardwire (10-ft) NEMA 5-20P (10-ft) NEMA L5-20P (10-ft) IEC320 C20 (10-ft)
Input Protection	N/A	N/A	N/A	Yes	Yes	Yes
Hydraulic-Magnetic Breakers	N/A	N/A	N/A	No	No	No
Max Input Current (A)	N/A	N/A	N/A	20 Amps	20 Amps	20 Amps
Surge-protection Joule Rating	N/A	N/A	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A	N/A	N/A
Earth-ground Lug	N/A	N/A	N/A	Yes	Yes	Yes
Output						
Output Voltage	120V	120V	120V	100V-127V	100V-127V	100V-127V
Maximum Output Rating (A)	N/A	N/A	N/A	16 Amps	16 Amps	16 Amps
Number of Output Circuits	N/A	N/A	N/A	One	One	One
Front Panel Receptacles (Qty)	(12) NEMA 5-20R	(12) NEMA 5-20R	(24) NEMA 5-20R	N/A	(16) NEMA 5-15/20R	(24) NEMA 5-15/20R
Rear Panel Receptacles (Qty)	N/A	N/A	N/A	(8) NEMA 5-15/20R	N/A	N/A
Management						
Web & SNMP Management	Yes	Yes	Yes	Yes	Yes	Yes
10/100/1000 Mbit Compatible	Yes	Yes	Yes	10/100	10/100	10/100
Network port Sharing	Yes	Yes	Yes	Yes	Yes	Yes
Individual Outlet Control	Yes	Yes	Yes	Yes	Yes	Yes
Individual Outlet Metering	No	No	No	No	No	No
Combined Outlet Metering	Yes	Yes	Yes	Yes	Yes	Yes
Multi-level User Access	N/A	N/A	N/A	Yes	Yes	Yes
On/Off Outlet Sequencing	Yes	Yes	Yes	Yes	Yes	Yes
On/Off Outlet Scheduling	N/A	N/A	N/A	Yes	Yes	Yes
Event Configuration	N/A	N/A	N/A	Yes	Yes	Yes
Outlet Grouping	Yes	Yes	Yes	Yes	Yes	Yes
Auto Ping Function	N/A	N/A	N/A	Yes	Yes	Yes
SNMP IPv4/IPv6 Compatible	N/A	N/A	N/A	Yes	Yes	Yes
SNMPv3 Compatible	N/A	N/A	N/A	Yes	Yes	Yes
SSH/SSL Compatible	N/A	N/A	N/A	Yes	Yes	Yes
TLS v1.2 or Greater	N/A	N/A	N/A	Yes	Yes	Yes
Env. Sensor Compatible	Yes	Yes	Yes	Yes	Yes	Yes
Flash Firmware Upgrades	N/A	N/A	N/A	Yes	Yes	Yes
Remote Batch Updates	N/A	N/A	N/A	N/A	N/A	N/A
Physical						
All-metal case	N/A	N/A	N/A	Yes	Yes	Yes
Installation Format (H/V)	Horizontal	Horizontal	Vertical	Horizontal (1U), Vertical (0U)	Vertical (0U)	Vertical (0U)
Color-coded Receptacles	Yes	Yes	Yes	No	No	No
Dimensions (HxWxD)	1.72" x 17" x 12"	1.72" x 17" x 12"	N/A	1.75" x 17.01" x 5.83"	49.02" x 2.20" x 3.07"	70.00" x 2.20" x 3.07"
Weight	10 lbs.	12 lbs.	N/A	7.72 lbs.	8.82 lbs.	13.22 lbs.
Warranty & Certifications						
62368-1 Certification	No	No	No	Yes	Yes	Yes
RoHS Compliant	Yes	Yes	Yes	Yes	Yes	Yes
TAA Compliant	Yes	Yes	Yes	Yes	Yes	Yes
Warranty	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years

All names and trademarks are the property of the respective companies.

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

(Competitor) Advantage in **BOLD**

(MM Advantage in **BOLD**)

Feature Comparison Chart of MM RPM Series vs. Vertiv rPDU Series

FEATURES	rPDU Series	Minuteman RPM Series		
	VP5N30A5	RPM308N1LCD-HW (-L30P)	RPM3016N1LCD-HW (-L30P)	RPM3024N1LCD-HW (-L30P)
Input				
On/Off Switch	N/A	No	No	No
Power On/Off LED	N/A	Yes	Yes	Yes
Input Voltage	120V	100V-127V	100V-127V	100V-127V
Input Plug (Cord Length)	NEMA L5-30P	Hardwire (10-ft) NEMA L6-30P (10-ft)	Hardwire (10-ft) NEMA L6-30P (10-ft)	Hardwire (10-ft) NEMA L6-30P (10-ft)
Input Protection	N/A	Yes	Yes	Yes
Hydraulic-Magnetic Breakers	N/A	No	No	No
Max Input Current (A)	N/A	30 Amps	30 Amps	30 Amps
Surge-protection Joule Rating	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A
Earth-ground Lug	N/A	Yes	Yes	Yes
Output				
Output Voltage	120V	100V-127V	100V-127V	100V-127V
Maximum Output Rating (A)	N/A	24 Amps	24 Amps	24 Amps
Number of Output Circuits	N/A	One	One	One
Front Panel Receptacles (Qty)	5-20R (24)	N/A	(16) NEMA 5-15/20R	(24) NEMA 5-15/20R
Rear Panel Receptacles (Qty)	N/A	(8) NEMA 5-15/20R	N/A	N/A
Management				
Web & SNMP Management	Yes	Yes	Yes	Yes
10/100/1000 Mbit Compatible	Yes	10/100	10/100	10/100
Network port Sharing	Yes	Yes	Yes	Yes
Individual Outlet Control	Yes	Yes	Yes	Yes
Individual Outlet Metering	No	No	No	No
Combined Outlet Metering	Yes	Yes	Yes	Yes
Multi-level User Access	N/A	Yes	Yes	Yes
On/Off Outlet Sequencing	Yes	Yes	Yes	Yes
On/Off Outlet Scheduling	N/A	Yes	Yes	Yes
Event Configuration	N/A	Yes	Yes	Yes
Outlet Grouping	Yes	Yes	Yes	Yes
Auto Ping Function	N/A	Yes	Yes	Yes
SNMP IPv4/IPv6 Compatible	N/A	Yes	Yes	Yes
SNMPv3 Compatible	N/A	Yes	Yes	Yes
SSH/SSL Compatible	N/A	Yes	Yes	Yes
TLS v1.2 or Greater	N/A	Yes	Yes	Yes
Env. Sensor Compatible	Yes	Yes	Yes	Yes
Flash Firmware Upgrades	N/A	Yes	Yes	Yes
Remote Batch Updates	N/A	N/A	N/A	N/A
Physical				
All-metal case	N/A	Yes	Yes	Yes
Installation Format (H/V)	Vertical	Horizontal/1U, Vertical/0U	Vertical (0U)	Vertical (0U)
Color-coded Receptacles	Yes	No	No	No
Dimensions (HxWxD)	N/A	1.76" x 17.00" x 8.50"	49.02" x 2.20" x 3.54"	70.00" x 2.20" x 3.54"
Weight	N/A	8.22 lbs.	9.26 lbs.	17.63 lbs.
Warranty & Certifications				
62368-1 Certification	No	Yes	Yes	Yes
RoHS Compliant	Yes	Yes	Yes	Yes
TAA Compliant	Yes	Yes	Yes	Yes
Warranty	3 Years	3 Years	3 Years	3 Years

and trademarks are the property of the respective companies.

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

(Competitor) Advantage in **BOLD**

(MM Advantage in **BOLD**)

Feature Comparison Chart of MM RPM Series vs. Vertiv rPDU Series*

FEATURES	rPDU Series	Minuteman RPM Series			
	VP5N20AB	RPM204I2LCD (-HW/-L20P)	RPM208I2LCD-L20P (-HW/-L20P)	RPM2016I2LCD-L20P (-HW/-L20P)	RPM2024I2LCD-L20P (-HW/-L20P)
Input					
On/Off Switch	N/A	No	No	No	No
Power On/Off LED	N/A	Yes	Yes	Yes	Yes
Input Voltage	208V	200V-240V	200V-240V	200V-240V	200V-240V
Input Plug (Cord Length)	NEMA L6-20P	Hardwire (10-ft) NEMA L6-20P (10-ft)	Hardwire (10-ft) NEMA L6-20P (10-ft)	Hardwire (10-ft) NEMA L6-20P (10-ft)	Hardwire (10-ft) NEMA L6-20P (10-ft)
Input Protection	N/A	Yes	Yes	Yes	Yes
Hydraulic-Magnetic Breakers	N/A	No	No	No	No
Max Input Current (A)	N/A	20 Amps	20 Amps	20 Amps	20 Amps
Surge-protection Joule Rating	N/A	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A	N/A
Earth-ground Lug	N/A	Yes	Yes	Yes	Yes
Output					
Output Voltage	208V	200V-240V	200V-240V	200V-240V	200V-240V
Maximum Output Rating (A)	N/A	16 Amps	16 Amps	16 Amps	16 Amps
Number of Output Circuits	N/A	One	One	One	One
Front Panel Receptacles (Qty)	(21) IEC320 C13, (3) IEC320 C19 (Locking)	N/A	N/A	(14) IEC320 C13, (2) IEC320 C19	(21) IEC320 C13, (3) IEC320 C19
Rear Panel Receptacles (Qty)	N/A	(4) IEC320 C13	(8) IEC320 C13	N/A	N/A
Management					
Web & SNMP Management	Yes	Yes	Yes	Yes	Yes
10/100/1000 Mbit Compatible	Yes	10/100	10/100	10/100	10/100
Network port Sharing	Yes	Yes	Yes	Yes	Yes
Individual Outlet Control	Yes	Yes	Yes	Yes	Yes
Individual Outlet Metering	No	No	No	No	No
Combined Outlet Metering	Yes	Yes	Yes	Yes	Yes
Multi-level User Access	N/A	Yes	Yes	Yes	Yes
On/Off Outlet Sequencing	Yes	Yes	Yes	Yes	Yes
On/Off Outlet Scheduling	N/A	Yes	Yes	Yes	Yes
Event Configuration	N/A	Yes	Yes	Yes	Yes
Outlet Grouping	Yes	Yes	Yes	Yes	Yes
Auto Ping Function	N/A	Yes	Yes	Yes	Yes
SNMP IPv4/IPv6 Compatible	N/A	Yes	Yes	Yes	Yes
SNMPv3 Compatible	N/A	Yes	Yes	Yes	Yes
SSH/SSL Compatible	N/A	Yes	Yes	Yes	Yes
TLS v1.2 or Greater	N/A	Yes	Yes	Yes	Yes
Env. Sensor Compatible	Yes	Yes	Yes	Yes	Yes
Flash Firmware Upgrades	N/A	Yes	Yes	Yes	Yes
Remote Batch Updates	N/A	N/A	N/A	N/A	N/A
Physical					
All-metal case	N/A	Yes	Yes	Yes	Yes
Installation Format (H/V)	Vertical	Horizontal (1U), Vertical (0U)	Horizontal (1U), Vertical (0U)	Vertical (0U)	Vertical (0U)
Color-coded Receptacles	N/A	No	No	No	No
Dimensions (HxWxD)	N/A	1.75" x 17.0" x 8.5"	1.75" x 17.01" x 8.50"	49.00" x 2.20" x 3.54"	74.41" x 2.20" x 4.33"
Weight	N/A	8.82 lbs.	8.82 lbs.	8.82 lbs.	13.32 lbs.
Warranty & Certifications					
62368-1 Certification	No	Yes	Yes	Yes	Yes
RoHS Compliant	Yes	Yes	Yes	Yes	Yes
TAA Compliant	Yes	Yes	Yes	Yes	Yes
Warranty	3 Years	3 Years	3 Years	3 Years	3 Years

All names and trademarks are the property of the respective companies.

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

(Competitor) Advantage in **BOLD**

(MM Advantage in **BOLD**)

Feature Comparison Chart of MM RPM Series vs. Vertiv rPDU Series*

FEATURES	rPDU Series				Minuteman RPM Series		
	VP5N31A1	VP7N30AU	VP5N30AU	VP7N30AN	RPM30812LCD (-HW/-L30P)	RPM301612LCD-HW (-HW/-L30P)	RPM302412LCD-HW (-HW/-L30P)
Input							
On/Off Switch	N/A	N/A	N/A	N/A	No	No	No
Power On/Off LED	N/A	N/A	N/A	N/A	Yes	Yes	Yes
Input Voltage	208V	208V	208V	208V	200V-240V	200V-240V	200V-240V
Input Plug (Cord Length)	NEMA L6-30P	NEMA L6-30P	NEMA L6-30P	NEMA L6-30P	Hardwire (10-ft) NEMA L6-30P (10-ft)	Hardwire (10-ft) NEMA L6-30P (10-ft)	Hardwire (10-ft) NEMA L6-30P (10-ft)
Input Protection	N/A	N/A	N/A	N/A	Yes	Yes	Yes
Hydraulic-Magnetic Breakers	N/A	N/A	N/A	N/A	No	No	No
Max Input Current (A)	N/A	N/A	N/A	N/A	30 Amps	30 Amps	30 Amps
Surge-protection Joule Rating	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Earth-ground Lug	N/A	N/A	N/A	N/A	Yes	Yes	Yes
Output							
Output Voltage	208V	208V	208V	208V	200V-240V	200V-240V	200V-240V
Maximum Output Rating (A)	N/A	N/A	N/A	N/A	24 Amps	24 Amps	24 Amps
Number of Output Circuits	N/A	N/A	N/A	N/A	One	One	One
Front Panel Receptacles (Qty)	(12) IEC320 C13/C19 (Combination)	(20) IEC320 C13, (4) IEC320 C19 (Locking)	(20) IEC320 C13, (4) IEC320 C19 (Locking)	(30) IEC320 C13, (6) IEC320 C19 (Locking)	N/A	(14) IEC320 C13, (2) IEC320 C19	(21) IEC320 C13, (3) IEC320 C19
Rear Panel Receptacles (Qty)	N/A	N/A	N/A	N/A	(8) IEC320 C13	N/A	N/A
Management							
Web & SNMP Management	Yes	Yes	Yes	Yes	Yes	Yes	Yes
10/100/1000 Mbit Compatible	Yes	Yes	Yes	Yes	10/100	10/100	10/100
Network port Sharing	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Individual Outlet Control	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Individual Outlet Metering	No	Yes	No	Yes	No	No	No
Combined Outlet Metering	Yes	No	Yes	No	Yes	Yes	Yes
Multi-level User Access	N/A	N/A	N/A	N/A	Yes	Yes	Yes
On/Off Outlet Sequencing	Yes	Yes	Yes	Yes	Yes	Yes	Yes
On/Off Outlet Scheduling	N/A	N/A	N/A	N/A	Yes	Yes	Yes
Event Configuration	N/A	N/A	N/A	N/A	Yes	Yes	Yes
Outlet Grouping	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Auto Ping Function	N/A	N/A	N/A	N/A	Yes	Yes	Yes
SNMP IPv4/IPv6 Compatible	N/A	N/A	N/A	N/A	Yes	Yes	Yes
SNMPv3 Compatible	N/A	N/A	N/A	N/A	Yes	Yes	Yes
SSH/SSL Compatible	N/A	N/A	N/A	N/A	Yes	Yes	Yes
TLS v1.2 or Greater	N/A	N/A	N/A	N/A	Yes	Yes	Yes
Env. Sensor Compatible	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Flash Firmware Upgrades	N/A	N/A	N/A	N/A	Yes	Yes	Yes
Remote Batch Updates	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Physical							
All-metal case	N/A	N/A	N/A	N/A	Yes	Yes	Yes
Installation Format (H/V)	Horizontal	Vertical	Vertical	Vertical	Horizontal (1U), Vertical (0U)	Vertical (0U)	Vertical (0U)
Color-coded Receptacles	Yes	Yes	Yes	Yes	No	No	No
Dimensions (HxWxD)	1.72" x 17" x 12"	N/A	N/A	N/A	1.75" x 17.01" x 8.50"	49.02" x 2.20" x 3.15"	70.00" x 2.20" x 3.54"
Weight	12 lbs.	N/A	N/A	N/A	9.70 lbs.	12.78 lbs.	17.63 lbs.
Warranty & Certifications							
62368-1 Certification	Yes	No	No	No	Yes	Yes	Yes
RoHS Compliant	Yes	Yes	Yes	Yes	Yes	Yes	Yes
TAA Compliant	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Warranty	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years

All names and trademarks are the property of the respective companies.

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

(Competitor) Advantage in **BOLD**

(MM Advantage in **BOLD**)

Feature Comparison Chart of MM RPM Series vs. Eaton Switched Series*

FEATURES	Switched PDU Series				Minuteman RPM Series				
	PDU15NETLX	PDUMH15NET2LX	PDUMH15NET	PDUMV15NETLX	RPM1521E	RPM1581HVN	RPM158N1LCD-HW (-15P /-IEC)	RPM1516N1LCD-HW (15P /-IEC)	RPM1524N1LCD-HW (-15P /-IEC)
Input									
On/Off Switch	No	No	No	No	Yes	No	No	No	No
Power On/Off LED	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Input Voltage	120V	120V	120V	120V	120V	100V-120V	100V-127V	100V-127V	100V-127V
Input Plug (Cord Length)	NEMA 5-15P (6-ft)	NEMA 5-15P (12-ft)	NEMA 5-15P (12-ft)	NEMA 5-15P (10-ft)	NEMA 5-15P (6-ft)	NEMA 5-15P (10-ft)	Hardwire (10-ft) NEMA 5-15P (10-ft) IEC C20 (10-ft)	Hardwire (10-ft) NEMA 5-15P (10-ft) IEC C20 (10-ft)	Hardwire (10-ft) NEMA 5-15P (10-ft) IEC C20 (10-ft)
Input Protection	No	No	No	No	Yes	Yes	Yes	Yes	Yes
Hydraulic-Magnetic Breakers	N/A	N/A	N/A	N/A	No	No	No	No	No
Max Input Current (A)	15 Amps	15 Amps	15 Amps	15 Amps	15 Amps	15 Amps	15 Amps	15 Amps	15 Amps
Surge-protection Joule Rating	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Earth-ground Lug	No	Yes	Yes	Yes	No	No	Yes	Yes	Yes
Output									
Output Voltage	120V	120V	120V	120V	120V	100V-120V	100V-127V	100V-127V	100V-127V
Maximum Output Rating (A)	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps	12 Amps
Number of Output Circuits	N/A	N/A	N/A	N/A	N/A	One	One	One	One
Front Panel Receptacles (Qty)	N/A	(8) NEMA 5-15R	(8) NEMA 5-15R	(16) NEMA 5-15R	N/A	(8) NEMA 5-15R	N/A	N/A	N/A
Rear Panel Receptacles (Qty)	(2) NEMA 5-15R	N/A	(8) NEMA 5-15R	N/A	(2) NEMA 5-15R	N/A	(8) NEMA 5-15R	(16) NEMA 5-15R	(24) NEMA 5-15R
Management									
Web & SNMP Management	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
10/100/1000 Mbit Compatible	10/100	10/100	10/100	10/100	N/A	N/A	10/100	10/100	10/100
Network port Sharing	N/A	N/A	N/A	No	Yes	Yes	Yes	Yes	Yes
Individual Outlet Control	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Individual Outlet Metering	N/A	No	No	No	No	No	No	No	No
Combined Outlet Metering	N/A	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Multi-level User Access	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
On/Off Outlet Sequencing	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
On/Off Outlet Scheduling	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Event Configuration	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Outlet Grouping	No	No	No	No	Yes	Yes	Yes	Yes	Yes
Auto Ping Function	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
SNMP IPv4/IPv6 Compatible	N/A	Yes	Yes	Yes	No	No	Yes	Yes	Yes
SNMPv3 Compatible	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
SSH/SSL Compatible	N/A	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
TLS v1.2 or Greater	N/A	N/A	N/A	N/A	Yes	Yes	Yes	Yes	Yes
Env. Sensor Compatible	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Flash Firmware Upgrades	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Remote Batch Updates	Yes	Yes	Yes	No	N/A	N/A	N/A	N/A	N/A
Physical									
All-metal case	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Installation Format (H/V)	Vertical (0U), Wallmount, Under-counter	Horizontal (1U), Vertical (0U), Wallmount, Under-Counter	Horizontal (1U)	Vertical (0U)	Horizontal	Horizontal (1U), Vertical (0U)	Horizontal (1U), Vertical (0U)	Vertical (0U)	Vertical (0U)
Color-coded Receptacles	No	No	No	No	No	No	No	No	No
Dimensions (HxWxD)	7" x 5" x 1.73"	N/A	1.75" x 17.5" x 15.5"	49" x 2.19" x 2.65"	1.7" x 4.9" x 7.17"	1.73" x 17" x 3.54"	1.75" x 5.83" x 17.01"	49.02" x 2.20" x 3.07"	70.00" x 2.20" x 3.07"
Weight	2.64 lbs.	N/A	12.5 lbs.	7 lbs.	1.78 lbs.	4.85 lbs.	7.72 lbs.	8.82 lbs.	13.22 lbs.
Warranty & Certifications									
62368-1 Certification	No	No	No	No	No	Yes	Yes	Yes	Yes
RoHS Compliant	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes
TAA Compliant	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Warranty	2 Years	2 Years	2 Years	2 Years	3 Years	3 Years	3 Years	3 Years	3 Years

All names and trademarks are the property of the respective companies.

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

(Competitor) Advantage in **BOLD**

(MM Advantage in **BOLD**)

Feature Comparison Chart of MM RPM Series vs. Eaton Switched Series*

FEATURES	Switched PDU Series			Minuteman RPM Series		
	PDUH20NET2LX	PDUH20NET	PDUMV20NETLX PDUMVR20NETLX	RPM208N1LCD-HW (-20P /-L20P /-IEC)	RPM2016N1LCD-HW (-20P/-L20P/-IEC)	RPM2024N1LCD-HW (-20P/-L20P/-IEC)
Input						
On/Off Switch	No	No	No	No	No	No
Power On/Off LED	Yes	Yes	Yes	Yes	Yes	Yes
Input Voltage	120V	120V	120V	100V-127V	100V-127V	100V-127V
Input Plug (Cord Length)	NEMA L5-20P (12-ft) (w/5-20P adapter)	NEMA L5-20P (w/5-20P adapter)	NEMA L5-20P	Hardwire (10-ft) NEMA 5-20P (10-ft) NEMA L5-20P (10-ft) IEC320 C20 (10-ft)	Hardwire (10-ft) NEMA 5-20P (10-ft) NEMA L5-20P (10-ft) IEC320 C20 (10-ft)	Hardwire (10-ft) NEMA 5-20P (10-ft) NEMA L5-20P (10-ft) IEC320 C20 (10-ft)
Input Protection	No	No	No	Yes	Yes	Yes
Hydraulic-Magnetic Breakers	N/A	N/A	N/A	No	No	No
Max Input Current (A)	20 Amps	20 Amps	20 Amps	20 Amps	20 Amps	20 Amps
Surge-protection Joule Rating	N/A	N/A	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A	N/A	N/A
Earth-ground Lug	Yes	Yes	Yes	Yes	Yes	Yes
Output						
Output Voltage	120V	120V	120V	100V-127V	100V-127V	100V-127V
Maximum Output Rating (A)	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps
Number of Output Circuits	N/A	N/A	N/A	One	One	One
Front Panel Receptacles (Qty)	(8) NEMA 5-15/20R	(8) NEMA 5-15/20R	(24) NEMA 5-15/20R	N/A	(16) NEMA 5-15/20R	(24) NEMA 5-15/20R
Rear Panel Receptacles (Qty)	N/A	(8) NEMA 5-15/20R	N/A	(8) NEMA 5-15/20R	N/A	N/A
Management						
Web & SNMP Management	Yes	Yes	Yes	Yes	Yes	Yes
10/100/1000 Mbit Compatible	10/100	10/100	10/100	10/100	10/100	10/100
Network port Sharing	No	No	No	Yes	Yes	Yes
Individual Outlet Control	Yes	Yes	Yes	Yes	Yes	Yes
Individual Outlet Metering	No	No	No/Yes	No	No	No
Combined Outlet Metering	Yes	Yes	Yes	Yes	Yes	Yes
Multi-level User Access	Yes	Yes	Yes	Yes	Yes	Yes
On/Off Outlet Sequencing	Yes	Yes	Yes	Yes	Yes	Yes
On/Off Outlet Scheduling	Yes	No	Yes	Yes	Yes	Yes
Event Configuration	Yes	Yes	Yes	Yes	Yes	Yes
Outlet Grouping	No	No	No	Yes	Yes	Yes
Auto Ping Function	Yes	Yes	Yes	Yes	Yes	Yes
SNMP IPv4/IPv6 Compatible	Yes	N/A	Yes	Yes	Yes	Yes
SNMPv3 Compatible	Yes	Yes	Yes	Yes	Yes	Yes
SSH/SSL Compatible	Yes	Yes	Yes	Yes	Yes	Yes
TLS v1.2 or Greater	N/A	N/A	N/A	Yes	Yes	Yes
Env. Sensor Compatible	Yes	Yes	Yes	Yes	Yes	Yes
Flash Firmware Upgrades	Yes	Yes	Yes	Yes	Yes	Yes
Remote Batch Updates	Yes	No	Yes	N/A	N/A	N/A
Physical						
All-metal case	Yes	Yes	Yes	Yes	Yes	Yes
Installation Format (H/V)	Horizontal (1U), Vertical (0U), Wallmount, Under-counter	Horizontal (1U)	Vertical (0U)	Horizontal (1U), Vertical (0U)	Vertical (0U)	Vertical (0U)
Color-coded Receptacles	No	No	No	No	No	No
Dimensions (HxWxD)	N/A	1.75" x 17.5" x 15.5"	70" x 2.19" x 2.65"	1.75" x 17.01" x 5.83"	49.02" x 2.20" x 3.07"	70.00" x 2.20" x 3.07"
Weight	5.9 lbs.	12.5 lbs.	8.5 lbs.	7.72 lbs.	8.82 lbs.	13.22 lbs.
Warranty & Certifications						
62368-1 Certification	No	No	No	Yes	Yes	Yes
RoHS Compliant	Yes	Yes	Yes	Yes	Yes	Yes
TAA Compliant	Yes	Yes	Yes	Yes	Yes	Yes
Warranty	2 Years	2 Years	2 Years	3 Years	3 Years	3 Years

All names and trademarks are the property of the respective companies.

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

(Competitor) Advantage in **BOLD**

(MM Advantage in **BOLD**)

Feature Comparison Chart of MM RPM Series vs. Eaton Switched Series*

FEATURES	Switched PDU		Minuteman RPM Series		
	PDUH30NET	PDUMV30NETLX PDUMVR30NETLX	RPM308N1LCD-HW (-L30P)	RPM3016N1LCD-HW (-L30P)	RPM3024N1LCD-HW (-L30P)
Input					
On/Off Switch	No	No	No	No	No
Power On/Off LED	Yes	Yes	Yes	Yes	Yes
Input Voltage	120V	120V	100V-127V	100V-127V	100V-127V
Input Plug (Cord Length)	NEMA L5-30P (10-ft)	NEMA L5-30P (10-ft)	Hardwire (10-ft) NEMA L6-30P (10-ft)	Hardwire (10-ft) NEMA L6-30P (10-ft)	Hardwire (10-ft) NEMA L6-30P (10-ft)
Input Protection	Yes, (2) 20 Amp Breaker	Yes, (2) 20 Amp Breaker	Yes	Yes	Yes
Hydraulic-Magnetic Breakers	No	No	No	No	No
Max Input Current (A)	30 Amps	30 Amps	30 Amps	30 Amps	30 Amps
Surge-protection Joule Rating	N/A	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A	N/A
Earth-ground Lug	No	Yes	Yes	Yes	Yes
Output					
Output Voltage	120V	120V	100V-127V	100V-127V	100V-127V
Maximum Output Rating (A)	24 Amps	24 Amps	24 Amps	24 Amps	24 Amps
Number of Output Circuits	N/A	N/A	One	One	One
Front Panel Receptacles (Qty)	N/A	(24) NEMA 5-15/20R	N/A	(16) NEMA 5-15/20R	(24) NEMA 5-15/20R
Rear Panel Receptacles (Qty)	(16) NEMA 5-15/20R	Optional	(8) NEMA 5-15/20R	N/A	N/A
Management					
Web & SNMP Management	Yes	Yes	Yes	Yes	Yes
10/100/1000 Mbit Compatible	10/100	10/100	10/100	10/100	10/100
Network port Sharing	N/A	N/A	Yes	Yes	Yes
Individual Outlet Control	Yes	No/Yes/	Yes	Yes	Yes
Individual Outlet Metering	No	Yes	No	No	No
Combined Outlet Metering	Yes	Yes	Yes	Yes	Yes
Multi-level User Access	Yes	Yes	Yes	Yes	Yes
On/Off Outlet Sequencing	Yes	Yes	Yes	Yes	Yes
On/Off Outlet Scheduling	Yes	Yes	Yes	Yes	Yes
Event Configuration	Yes	Yes	Yes	Yes	Yes
Outlet Grouping	Yes	Yes	Yes	Yes	Yes
Auto Ping Function	Yes	Yes	Yes	Yes	Yes
SNMP IPv4/IPv6 Compatible	Yes	Yes	Yes	Yes	Yes
SNMPv3 Compatible	Yes	Yes	Yes	Yes	Yes
SSH/SSL Compatible	Yes	Yes	Yes	Yes	Yes
TLS v1.2 or Greater	N/A	N/A	Yes	Yes	Yes
Env. Sensor Compatible	Yes	Yes	Yes	Yes	Yes
Flash Firmware Upgrades	Yes	Yes	Yes	Yes	Yes
Remote Batch Updates	Yes	Yes	N/A	N/A	N/A
Physical					
All-metal case	Yes	Yes	Yes	Yes	Yes
Installation Format (H/V)	Horizontal (2U)	Vertical (0U)	Horizontal/1U, Vertical/0U	Vertical (0U)	Vertical (0U)
Color-coded Receptacles	No	No	No	No	No
Dimensions (HxWxD)	3.5" x 17.5" x 12.5"	70" x 2.2" x 2.05"	1.76" x 17.00" x 8.50"	49.02" x 2.20" x 3.54"	70.00" x 2.20" x 3.54"
Weight	13.8 lbs.	9.94 lbs.	8.22 lbs.	9.26 lbs.	17.63 lbs.
Warranty & Certifications					
62368-1 Certification	No	No	Yes	Yes	Yes
RoHS Compliant	Yes	Yes	Yes	Yes	Yes
TAA Compliant	Yes	Yes	Yes	Yes	Yes
Warranty	2 Years	2 Years	3 Years	3 Years	3 Years

*and trademarks are the property of the respective companies.

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

(Competitor) Advantage in **BOLD**

(MM Advantage in **BOLD**)

Feature Comparison Chart of MM RPM Series vs. Eaton Switched Series*

FEATURES	Switched PDU Series		Minuteman RPM Series			
	PDUMH20HVNET	PDUMV20HVNETLX	RPM204I2LCD (-HW/-L20P)	RPM208I2LCD-L20P (-HW/-L20P)	RPM2016I2LCD-L20P (-HW/-L20P)	RPM2024I2LCD-L20P (-HW/-L20P)
Input						
On/Off Switch	No	No	No	No	No	No
Power On/Off LED	Yes	Yes	Yes	Yes	Yes	Yes
Input Voltage	208V-230V	208V-230V	200V-240V	200V-240V	200V-240V	200V-240V
Input Plug (Cord Length)	IEC320 C20 to L6-20P (8-ft)	IEC320 C20 to L6-20P (10-ft)	Hardwire (10-ft) NEMA L6-20P (10-ft)	Hardwire (10-ft) NEMA L6-20P (10-ft)	Hardwire (10-ft) NEMA L6-20P (10-ft)	Hardwire (10-ft) NEMA L6-20P (10-ft)
Input Protection	No	No	Yes	Yes	Yes	Yes
Hydraulic-Magnetic Breakers	N/A	N/A	No	No	No	No
Max Input Current (A)	20 Amps	20 Amps	20 Amps	20 Amps	20 Amps	20 Amps
Surge-protection Joule Rating	N/A	N/A	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A	N/A	N/A
Earth-ground Lug	Yes	Yes	Yes	Yes	Yes	Yes
Output						
Output Voltage	208V-230V	208V-230V	200V-240V	200V-240V	200V-240V	200V-240V
Maximum Output Rating (A)	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps
Number of Output Circuits	N/A	N/A	One	One	One	One
Front Panel Receptacles (Qty)	(8) IEC320 C13	(20) IEC320 C13, (4) IEC320 C19	N/A	N/A	(14) IEC320 C13, (2) IEC320 C19	(21) IEC320 C13, (3) IEC320 C19
Rear Panel Receptacles (Qty)	N/A	N/A	(4) IEC320 C13	(8) IEC320 C13	N/A	N/A
Management						
Web & SNMP Management	Yes	Yes	Yes	Yes	Yes	Yes
10/100/1000 Mbit Compatible	10/100	10/100	10/100	10/100	10/100	10/100
Network port Sharing	No	No	Yes	Yes	Yes	Yes
Individual Outlet Control	Yes	Yes	Yes	Yes	Yes	Yes
Individual Outlet Metering	No	No	No	No	No	No
Combined Outlet Metering	Yes	Yes	Yes	Yes	Yes	Yes
Multi-level User Access	Yes	Yes	Yes	Yes	Yes	Yes
On/Off Outlet Sequencing	Yes	Yes	Yes	Yes	Yes	Yes
On/Off Outlet Scheduling	No	No	Yes	Yes	Yes	Yes
Event Configuration	Yes	Yes	Yes	Yes	Yes	Yes
Outlet Grouping	No	No	Yes	Yes	Yes	Yes
Auto Ping Function	Yes	Yes	Yes	Yes	Yes	Yes
SNMP IPv4/IPv6 Compatible	N/A	N/A	Yes	Yes	Yes	Yes
SNMPv3 Compatible	Yes	Yes	Yes	Yes	Yes	Yes
SSH/SSL Compatible	Yes	Yes	Yes	Yes	Yes	Yes
TLS v1.2 or Greater	N/A	N/A	Yes	Yes	Yes	Yes
Env. Sensor Compatible	Yes	Yes	Yes	Yes	Yes	Yes
Flash Firmware Upgrades	Yes	Yes	Yes	Yes	Yes	Yes
Remote Batch Updates	No	No	N/A	N/A	N/A	N/A
Physical						
All-metal case	Yes	Yes	Yes	Yes	Yes	Yes
Installation Format (H/V)	Horizontal (1U)	Vertical (0U)	Horizontal (1U), Vertical (0U)	Horizontal (1U), Vertical (0U)	Vertical (0U)	Vertical (0U)
Color-coded Receptacles	No	No	No	No	No	No
Dimensions (HxWxD)	1.72" x 14.77" x 17.33"	70" x 2.19" x 2.65"	1.75" x 17.0" x 8.5"	1.75" x 17.01" x 8.50"	49.00" x 2.20" x 3.54"	74.41" x 2.20" x 4.33"
Weight	9 lbs.	8.5 lbs.	8.82 lbs.	8.82 lbs.	8.82 lbs.	13.32 lbs.
Warranty & Certifications						
62368-1 Certification	No	No	Yes	Yes	Yes	Yes
RoHS Compliant	Yes	Yes	Yes	Yes	Yes	Yes
TAA Compliant	Yes	Yes	Yes	Yes	Yes	Yes
Warranty	2 Years	2 Years	3 Years	3 Years	3 Years	3 Years

All names and trademarks are the property of the respective companies.

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

(Competitor) Advantage in **BOLD**

(MM Advantage in **BOLD**)

Feature Comparison Chart of MM RPM Series vs. Eaton Switched Series*

FEATURES	Switched PDU Series			Minuteman RPM Series		
	PDU MH30HV19NET	PDU MH30HVNET	PDU MVNETLX PDU MV30HVNETLX PDU MV30RHVNETLX	RPM308I2LCD (-HW/-L30P)	RPM3016I2LCD-HW (-HW/-L30P)	RPM3024I2LCD-HW (-HW/-L30P)
Input						
On/Off Switch	No	No	No	No	No	No
Power On/Off LED	Yes	Yes	Yes	Yes	Yes	Yes
Input Voltage	208-230V	208-230V	208-230V	200V-240V	200V-240V	200V-240V
Input Plug (Cord Length)	NEMA L6-30P (15-ft)	NEMA L6-30P (12-ft)	NEMA L6-30P (10-ft)	Hardwire (10-ft) NEMA L6-30P (10-ft)	Hardwire (10-ft) NEMA L6-30P (10-ft)	Hardwire (10-ft) NEMA L6-30P (10-ft)
Input Protection	Yes, (3) 20 Amp Breaker	Yes, (2) 15 Amp Breaker	Yes, (2) 20 Amp Breaker	Yes	Yes	Yes
Hydraulic-Magnetic Breakers	No	No	No	No	No	No
Max Input Current (A)	30 Amps	30 Amps	30 Amps	30 Amps	30 Amps	30 Amps
Surge-protection Joule Rating	N/A	N/A	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A	N/A	N/A
Earth-ground Lug	Yes	No	Yes	Yes	Yes	Yes
Output						
Output Voltage	208V-230V	208V-230V	208V-230V	200V-240V	200V-240V	200V-240V
Maximum Output Rating (A)	24 Amps	24 Amps	24 Amps	24 Amps	24 Amps	24 Amps
Number of Output Circuits	N/A	N/A	N/A	One	One	One
Front Panel Receptacles (Qty)	N/A	N/A	(20) IEC320 C13, (4) IEC320 C19	N/A	(14) IEC320 C13, (2) IEC320 C19	(21) IEC320 C13, (3) IEC320 C19
Rear Panel Receptacles (Qty)	(8) IEC320 C13, (6) IEC320 C19	(16) IEC320 C13	Optional	(8) IEC320 C13	N/A	N/A
Management						
Web & SNMP Management	Yes	Yes	Yes	Yes	Yes	Yes
10/100/1000 Mbit Compatible	10/100	10/100	10/100	10/100	10/100	10/100
Network port Sharing	N/A	N/A	N/A	Yes	Yes	Yes
Individual Outlet Control	Yes	Yes	Yes	Yes	Yes	Yes
Individual Outlet Metering	No	No	No/Yes	No	No	No
Combined Outlet Metering	Yes	Yes	Yes	Yes	Yes	Yes
Multi-level User Access	Yes	Yes	Yes	Yes	Yes	Yes
On/Off Outlet Sequencing	Yes	Yes	Yes	Yes	Yes	Yes
On/Off Outlet Scheduling	Yes	Yes	Yes	Yes	Yes	Yes
Event Configuration	Yes	Yes	Yes	Yes	Yes	Yes
Outlet Grouping	Yes	Yes	Yes	Yes	Yes	Yes
Auto Ping Function	Yes	Yes	Yes	Yes	Yes	Yes
SNMP IPv4/IPv6 Compatible	N/A	N/A	Yes	Yes	Yes	Yes
SNMPv3 Compatible	N/A	N/A	Yes	Yes	Yes	Yes
SSH/SSL Compatible	Yes	Yes	Yes	Yes	Yes	Yes
TLS v1.2 or Greater	N/A	N/A	N/A	Yes	Yes	Yes
Env. Sensor Compatible	Yes	Yes	Yes	Yes	Yes	Yes
Flash Firmware Upgrades	Yes	Yes	Yes	Yes	Yes	Yes
Remote Batch Updates	Yes	Yes	Yes	N/A	N/A	N/A
Physical						
All-metal case	Yes	Yes	Yes	Yes	Yes	Yes
Installation Format (H/V)	Horizontal (2U)	Horizontal (2U), Wallmount, Under-counter	Vertical (0U)	Horizontal (1U), Vertical (0U)	Vertical (0U)	Vertical (0U)
Color-coded Receptacles	No	No	No	No	No	No
Dimensions (HxWxD)	3.5" x 17.5" x 12.5	3.5" x 17.5" x 12.5"	70" x 2.19" x 2.65"	1.75" x 17.01" x 8.50"	49.02" x 2.20" x 3.15"	70.00" x 2.20" x 3.54"
Weight	13.8 lbs.	13.8 lbs.	11.5 lbs.	9.70 lbs.	12.78 lbs.	17.63 lbs.
Warranty & Certifications						
62368-1 Certification	No	No	No	Yes	Yes	Yes
RoHS Compliant	Yes	Yes	Yes	Yes	Yes	Yes
TAA Compliant	Yes	Yes	Yes	Yes	Yes	Yes
Warranty	2 Years	2 Years	2 Years	3 Years	3 Years	3 Years

All names and trademarks are the property of the respective companies.

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

(Competitor) Advantage in **BOLD**

(MM Advantage in **BOLD**)

Comparison Chart of MM RPM Series vs. Chatsworth Switched eConnect

FEATURES	eConnect PDU Series	Minuteman RPM Series		
	EA-5001-C (-E / -CE)	RPM208N1LCD-HW (-20P / -L20P / -IEC)	RPM2016N1LCD-HW (-20P / -L20P / -IEC)	RPM2024N1LCD-HW (-20P / -L20P / -IEC)
Input				
On/Off Switch	No	No	No	No
Power On/Off LED	Yes	Yes	Yes	Yes
Input Voltage	120V	100V-127V	100V-127V	100V-127V
Input Plug (Cord Length)	IEC320 C20 to NEMA L5-20P (10-ft)	Hardwire (10-ft) NEMA 5-20P (10-ft) NEMA L5-20P (10-ft) IEC320 C20 (10-ft)	Hardwire (10-ft) NEMA 5-20P (10-ft) NEMA L5-20P (10-ft) IEC320 C20 (10-ft)	Hardwire (10-ft) NEMA 5-20P (10-ft) NEMA L5-20P (10-ft) IEC320 C20 (10-ft)
Input Protection	No	Yes	Yes	Yes
Hydraulic-Magnetic Breakers	N/A	No	No	No
Max Input Current (A)	20 Amps	20 Amps	20 Amps	20 Amps
Surge-protection Joule Rating	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A
Earth-ground Lug	Yes	Yes	Yes	Yes
Output				
Output Voltage	120V	100V-127V	100V-127V	100V-127V
Maximum Output Rating (A)	16 Amps	16 Amps	16 Amps	16 Amps
Number of Output Circuits	N/A	One	One	One
Front Panel Receptacles (Qty)	(24) NEMA 5-15/20R	N/A	(16) NEMA 5-15/20R	(24) NEMA 5-15/20R
Rear Panel Receptacles (Qty)	N/A	(8) NEMA 5-15/20R	N/A	N/A
Management				
Web & SNMP Management	Yes	Yes	Yes	Yes
10/100/1000 Mbit Compatible	Yes	10/100	10/100	10/100
Network port Sharing	Yes	Yes	Yes	Yes
Individual Outlet Control	Yes	Yes	Yes	Yes
Individual Outlet Metering	No	No	No	No
Combined Outlet Metering	Yes	Yes	Yes	Yes
Multi-level User Access	Yes	Yes	Yes	Yes
On/Off Outlet Sequencing	Yes	Yes	Yes	Yes
On/Off Outlet Scheduling	No	Yes	Yes	Yes
Event Configuration	Yes	Yes	Yes	Yes
Outlet Grouping	Yes	Yes	Yes	Yes
Auto Ping Function	No, Manual	Yes	Yes	Yes
SNMP IPv4/IPv6 Compatible	Yes	Yes	Yes	Yes
SNMPv3 Compatible	Yes	Yes	Yes	Yes
SSH/SSL Compatible	Yes	Yes	Yes	Yes
TLS v1.2 or Greater	N/A	Yes	Yes	Yes
Env. Sensor Compatible	Yes	Yes	Yes	Yes
Flash Firmware Upgrades	Yes	Yes	Yes	Yes
Remote Batch Updates	Yes	N/A	N/A	N/A
Physical				
All-metal case	Yes	Yes	Yes	Yes
Installation Format (H/V)	Vertical (0U)	Horizontal (1U), Vertical (0U)	Vertical (0U)	Vertical (0U)
Color-coded Receptacles	Yes	No	No	No
Dimensions (HxWxD)	71.9" x 2.2" x 2.8"	1.75" x 17.01" x 5.83"	49.02" x 2.20" x 3.07"	70.00" x 2.20" x 3.07"
Weight	18 lbs.	7.72 lbs.	8.82 lbs.	13.22 lbs.
Warranty & Certifications				
62368-1 Certification	Yes	Yes	Yes	Yes
RoHS Compliant	Yes	Yes	Yes	Yes
TAA Compliant	Yes	Yes	Yes	Yes
Warranty	3 Years	3 Years	3 Years	3 Years

All names and trademarks are the property of the respective companies.

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

(Competitor) Advantage in **BOLD**

(MM Advantage in **BOLD**)

Feature Comparison Chart of MM RPM Series vs. Chatsworth S

FEATURES	eConnect PDU Series	Minuteman RPM Series		
	EA-5002-C (-E / -CE)	RPM308N1LCD-HW (-L30P)	RPM3016N1LCD-HW (-L30P)	RPM3024N1LCD-HW (-L30P)
Input				
On/Off Switch	No	No	No	No
Power On/Off LED	Yes	Yes	Yes	Yes
Input Voltage	120V	100V-127V	100V-127V	100V-127V
Input Plug (Cord Length)	L5-30P (10-ft)	Hardwire (10-ft) NEMA L6-30P (10-ft)	Hardwire (10-ft) NEMA L6-30P (10-ft)	Hardwire (10-ft) NEMA L6-30P (10-ft)
Input Protection	Yes, (2) 20 Amp	Yes	Yes	Yes
Hydraulic-Magnetic Breakers	Yes	No	No	No
Max Input Current (A)	30 Amps	30 Amps	30 Amps	30 Amps
Surge-protection Joule Rating	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A
Earth-ground Lug	Yes	Yes	Yes	Yes
Output				
Output Voltage	120V	100V-127V	100V-127V	100V-127V
Maximum Output Rating (A)	24 Amps	24 Amps	24 Amps	24 Amps
Number of Output Circuits	N/A	One	One	One
Front Panel Receptacles (Qty)	(24) NEMA 5-15/20R	N/A	(16) NEMA 5-15/20R	(24) NEMA 5-15/20R
Rear Panel Receptacles (Qty)	N/A	(8) NEMA 5-15/20R	N/A	N/A
Management				
Web & SNMP Management	Yes	Yes	Yes	Yes
10/100/1000 Mbit Compatible	Yes	10/100	10/100	10/100
Network port Sharing	Yes	Yes	Yes	Yes
Individual Outlet Control	Yes	Yes	Yes	Yes
Individual Outlet Metering	No	No	No	No
Combined Outlet Metering	Yes	Yes	Yes	Yes
Multi-level User Access	Yes	Yes	Yes	Yes
On/Off Outlet Sequencing	Yes	Yes	Yes	Yes
On/Off Outlet Scheduling	No	Yes	Yes	Yes
Event Configuration	Yes	Yes	Yes	Yes
Outlet Grouping	Yes	Yes	Yes	Yes
Auto Ping Function	No, Manual	Yes	Yes	Yes
SNMP IPv4/IPv6 Compatible	Yes	Yes	Yes	Yes
SNMPv3 Compatible	Yes	Yes	Yes	Yes
SSH/SSL Compatible	Yes	Yes	Yes	Yes
TLS v1.2 or Greater	N/A	Yes	Yes	Yes
Env. Sensor Compatible	Yes	Yes	Yes	Yes
Flash Firmware Upgrades	Yes	Yes	Yes	Yes
Remote Batch Updates	Yes	N/A	N/A	N/A
Physical				
All-metal case	Yes	Yes	Yes	Yes
Installation Format (H/V)	Vertical (0U)	Horizontal/1U, Vertical/0U	Vertical (0U)	Vertical (0U)
Color-coded Receptacles	Yes	No	No	No
Dimensions (HxWxD)	71.9" x 2.2" x 2.8"	1.76" x 17.00" x 8.50"	49.02" x 2.20" x 3.54"	70.00" x 2.20" x 3.54"
Weight	18 lbs.	8.22 lbs.	9.26 lbs.	17.63 lbs.
Warranty & Certifications				
62368-1 Certification	Yes	Yes	Yes	Yes
RoHS Compliant	Yes	Yes	Yes	Yes
TAA Compliant	Yes	Yes	Yes	Yes
Warranty	3 Years	3 Years	3 Years	3 Years

and trademarks are the property of the respective companies.

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

(Competitor) Advantage in **BOLD**

(MM Advantage in **BOLD**)

Feature Comparison Chart of MM RPM Series vs. Chatsworth Switched eConnect PDU

FEATURES	eConnect PDU Series		Minuteman RPM Series			
	EA-5069-C (-E / -CE)	EA-5070-C (-E / -CE)	RPM204I2LCD (-HW/-L20P)	RPM208I2LCD-L20P (-HW/-L20P)	RPM2016I2LCD-L20P (-HW/-L20P)	RPM2024I2LCD-L20P (-HW/-L20P)
Input						
On/Off Switch	No	No	No	No	No	No
Power On/Off LED	Yes	Yes	Yes	Yes	Yes	Yes
Input Voltage	208V	208V	200V-240V	200V-240V	200V-240V	200V-240V
Input Plug (Cord Length)	L6-20P (10-ft)	C20 to NEMA L6-20P (10-ft).	Hardwire (10-ft) NEMA L6-20P (10-ft)	Hardwire (10-ft) NEMA L6-20P (10-ft)	Hardwire (10-ft) NEMA L6-20P (10-ft)	Hardwire (10-ft) NEMA L6-20P (10-ft)
Input Protection	No	No	Yes	Yes	Yes	Yes
Hydraulic-Magnetic Breakers	N/A	N/A	No	No	No	No
Max Input Current (A)	20 Amps	20 Amps	20 Amps	20 Amps	20 Amps	20 Amps
Surge-protection Joule Rating	N/A	N/A	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A	N/A	N/A
Earth-ground Lug	Yes	Yes	Yes	Yes	Yes	Yes
Output						
Output Voltage	208V	208V	200V-240V	200V-240V	200V-240V	200V-240V
Maximum Output Rating (A)	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps	16 Amps
Number of Output Circuits	N/A	N/A	One	One	One	One
Front Panel Receptacles (Qty)	(18) IEC320 C13, (6) IEC320 C19	(18) IEC320 C13, (6) IEC320 C19	N/A	N/A	(14) IEC320 C13, (2) IEC320 C19	(21) IEC320 C13, (3) IEC320 C19
Rear Panel Receptacles (Qty)	N/A	N/A	(4) IEC320 C13	(8) IEC320 C13	N/A	N/A
Management						
Web & SNMP Management	Yes	Yes	Yes	Yes	Yes	Yes
10/100/1000 Mbit Compatible	Yes	Yes	10/100	10/100	10/100	10/100
Network port Sharing	Yes	Yes	Yes	Yes	Yes	Yes
Individual Outlet Control	Yes	Yes	Yes	Yes	Yes	Yes
Individual Outlet Metering	No	No	No	No	No	No
Combined Outlet Metering	Yes	Yes	Yes	Yes	Yes	Yes
Multi-level User Access	Yes	Yes	Yes	Yes	Yes	Yes
On/Off Outlet Sequencing	Yes	Yes	Yes	Yes	Yes	Yes
On/Off Outlet Scheduling	No	No	Yes	Yes	Yes	Yes
Event Configuration	Yes	Yes	Yes	Yes	Yes	Yes
Outlet Grouping	Yes	Yes	Yes	Yes	Yes	Yes
Auto Ping Function	No, Manual	No, Manual	Yes	Yes	Yes	Yes
SNMP IPv4/IPv6 Compatible	Yes	Yes	Yes	Yes	Yes	Yes
SNMPv3 Compatible	Yes	Yes	Yes	Yes	Yes	Yes
SSH/SSL Compatible	Yes	Yes	Yes	Yes	Yes	Yes
TLS v1.2 or Greater	N/A	N/A	Yes	Yes	Yes	Yes
Env. Sensor Compatible	Yes	Yes	Yes	Yes	Yes	Yes
Flash Firmware Upgrades	Yes	Yes	Yes	Yes	Yes	Yes
Remote Batch Updates	Yes	Yes	N/A	N/A	N/A	N/A
Physical						
All-metal case	Yes	Yes	Yes	Yes	Yes	Yes
Installation Format (H/V)	Vertical (0U)	Vertical (0U)	Horizontal (1U), Vertical (0U)	Horizontal (1U), Vertical (0U)	Vertical (0U)	Vertical (0U)
Color-coded Receptacles	Yes	Yes	No	No	No	No
Dimensions (HxWxD)	71.9" x 2.2" x 2.8"	71.9" x 2.2" x 2.8"	1.75" x 17.0" x 8.5"	1.75" x 17.01" x 8.50"	49.00" x 2.20" x 3.54"	74.41" x 2.20" x 4.33"
Weight	18 lbs.	18 lbs.	8.82 lbs.	8.82 lbs.	8.82 lbs.	13.32 lbs.
Warranty & Certifications						
62368-1 Certification	Yes	Yes	Yes	Yes	Yes	Yes
RoHS Compliant	Yes	Yes	Yes	Yes	Yes	Yes
TAA Compliant	Yes	Yes	Yes	Yes	Yes	Yes
Warranty	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years

All names and trademarks are the property of the respective companies.

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

(Competitor) Advantage in **BOLD**

(MM Advantage in **BOLD**)

Feature Comparison Chart of MM RPM Series vs. Chatsworth Switched

FEATURES	eConnect PDU Series		Minuteman RPM Series		
	EA-5004-C (-E / -CE)	EA-5012-C (-E / -CE)	RPM308I2LCD (-HW/-L30P)	RPM3016I2LCD-HW (-HW/-L30P)	RPM3024I2LCD-HW (-HW/-L30P)
Input					
On/Off Switch	No	No	No	No	No
Power On/Off LED	Yes	Yes	Yes	Yes	Yes
Input Voltage	208V	208V	200V-240V	200V-240V	200V-240V
Input Plug (Cord Length)	NEMA L6-30P (10-ft)	NEMA L6-30P	Hardwire (10-ft) NEMA L6-30P (10-ft)	Hardwire (10-ft) NEMA L6-30P (10-ft)	Hardwire (10-ft) NEMA L6-30P (10-ft)
Input Protection	Yes, (2) 20 Amp	Yesm (2) 20 Amp	Yes	Yes	Yes
Hydraulic-Magnetic Breakers	Yes	Yes	No	No	No
Max Input Current (A)	30 Amps	30 Amps	30 Amps	30 Amps	30 Amps
Surge-protection Joule Rating	N/A	N/A	N/A	N/A	N/A
Surge LED Indicator	N/A	N/A	N/A	N/A	N/A
Earth-ground Lug	Yes	Yes	Yes	Yes	Yes
Output					
Output Voltage	208V	208V	200V-240V	200V-240V	200V-240V
Maximum Output Rating (A)	24 Amps	24 Amps	24 Amps	24 Amps	24 Amps
Number of Output Circuits	N/A	N/A	One	One	One
Front Panel Receptacles (Qty)	(24) IEC320 C13	(18) IEC320 C13, (6) IEC320 C19	N/A	(14) IEC320 C13, (2) IEC320 C19	(21) IEC320 C13, (3) IEC320 C19
Rear Panel Receptacles (Qty)	N/A	N/A	(8) IEC320 C13	N/A	N/A
Management					
Web & SNMP Management	Yes	Yes	Yes	Yes	Yes
10/100/1000 Mbit Compatible	Yes	Yes	10/100	10/100	10/100
Network port Sharing	Yes	Yes	Yes	Yes	Yes
Individual Outlet Control	Yes	Yes	Yes	Yes	Yes
Individual Outlet Metering	No	No	No	No	No
Combined Outlet Metering	Yes	Yes	Yes	Yes	Yes
Multi-level User Access	Yes	Yes	Yes	Yes	Yes
On/Off Outlet Sequencing	Yes	Yes	Yes	Yes	Yes
On/Off Outlet Scheduling	No	No	Yes	Yes	Yes
Event Configuration	Yes	Yes	Yes	Yes	Yes
Outlet Grouping	Yes	Yes	Yes	Yes	Yes
Auto Ping Function	No, Manual	No, Manual	Yes	Yes	Yes
SNMP IPv4/IPv6 Compatible	Yes	Yes	Yes	Yes	Yes
SNMPv3 Compatible	Yes	Yes	Yes	Yes	Yes
SSH/SSL Compatible	Yes	Yes	Yes	Yes	Yes
TLS v1.2 or Greater	N/A	N/A	Yes	Yes	Yes
Env. Sensor Compatible	Yes	Yes	Yes	Yes	Yes
Flash Firmware Upgrades	Yes	Yes	Yes	Yes	Yes
Remote Batch Updates	Yes	Yes	N/A	N/A	N/A
Physical					
All-metal case	Yes	Yes	Yes	Yes	Yes
Installation Format (H/V)	Vertical (0U)	Vertical (0U)	Horizontal (1U), Vertical (0U)	Vertical (0U)	Vertical (0U)
Color-coded Receptacles	Yes	Yes	No	No	No
Dimensions (HxWxD)	71.9" x 2.2" x 2.8"	71.9" x 2.2" x 2.8"	1.75" x 17.01" x 8.50"	49.02" x 2.20" x 3.15"	70.00" x 2.20" x 3.54"
Weight	18 lbs.	18 lbs.	9.70 lbs.	12.78 lbs.	17.63 lbs.
Warranty & Certifications					
62368-1 Certification	Yes	Yes	Yes	Yes	Yes
RoHS Compliant	Yes	Yes	Yes	Yes	Yes
TAA Compliant	Yes	Yes	Yes	Yes	Yes
Warranty	3 Years	3 Years	3 Years	3 Years	3 Years

All names and trademarks are the property of the respective companies.

MINUTEMAN attempts to maintain complete accuracy, however any of the features listed above may change without notice. MINUTEMAN assumes no responsibility for those changes.

(Competitor) Advantage in **BOLD)**

(MM Advantage in **BOLD)**