

**Endeavor<sup>®</sup> 6/10kVA Tower**  
**On-line Uninterruptible Power Supply**

## True On-line UPS Provides Maximum Protection

### Endeavor<sup>®</sup> 6/10kVA Uninterruptible Power Supply

The Minuteman<sup>®</sup> Endeavor<sup>®</sup> 6/10kVA Tower Series UPS combines transient free, pure sine wave output and extended runtime capability for critical applications. A front panel LCD display provides visual notification of the UPS status, including AC input status, battery status, and UPS fault indication.

### Ultra-Configurable Value for Large Systems

The Endeavor Series is available in two models with configuration options and multiple voltage configurations to ensure a proper solution is available for most applications. Both Endeavor models include 208-240V input and 120/208/230/240VAC output. Additional accessories, including an SNMP communication card and one or more external battery packs would further tailor the Endeavor to individual's needs.

A perfectly regulated, continuous sine wave output with zero transfer time offers guaranteed uptime and compatibility with all equipment types.

### Optional Accessories

- SNMP communication card: NetAgent-SNMP-ED
- Battery pack: BP240TWR

### Typical Applications

- Network Data Centers
- Remote Network Closets
- Security Systems
- Highly-sensitive Equipment
- Education Networks
- DAS and Small Cell Systems
- Telephone and VOIP Systems



# Endeavor® 6/10kVA Tower On-line Uninterruptible Power Supply

	FEATURES	ED6KTF	ED10KTF
General Features	Maximum Power Capacity	6000VA	10000VA
	Default Watt Capacity*	6000 Watts	10000 Watts
	Power Factor*	1.0	
	Topology	Double-conversion on-line	
	Input Type	Hardwire Terminal Block (L-N-G)	
	Output Type	Hardwire Terminal Block (L-N-G)	
Input	Number of Phases	Single - Phase	
	Nominal Voltage	208VAC ~ 240VAC	
	Acceptable Input Voltage	0 – 300VAC	
	Voltage Range	110 – 300VAC ±3%	
	Power Factor Correction	≥99% at Full Load	
	Frequency Limits	50/60Hz ±4Hz	
	Low Voltage Transfer Point	110VAC ±3% at 0-60% Load 176VAC ±3% at 60%-100% Load	
	High Voltage Transfer Point	120VAC ±3% at 0-60% Load 186VAC ±3% at 60%-100% Load	
	Input Protection	Re-settable Circuit Breaker and Fuse	
Output: Online	Nominal Range	240VAC (208/230/240 configurable) / 120VAC	
	Voltage Regulation	±2%	
	Frequency Range	50/60Hz ±4Hz	
	Efficiency (Online Mode)	≥89% (at Full Load)	
Output: Battery	Waveform Type	True Sine Wave	
	Nominal Voltage	240VAC (208/230/240 configurable) / 120VAC	
	Voltage Regulation	±2%	
	Frequency Range	50/60Hz +/-0.1Hz (unless synchronized to utility)	
	Voltage T.H.D.	≤ 2% @ 100% Linear Load; ≤ 8% @ 100% Non-linear Load	
	Dynamic Response	200ms to normal voltage±2%	
	Transfer Time	0 ms	
	Slew Rate	60V/ms	
	Crest Factor	2.6:1 max	
	Overload Capacity	≥100.1% - ≤110% for 30 secs. / ≥110.1% - ≤130% for 10 secs. / ≥130.1% for 1 sec.	
Battery	System Voltage	240VDC	
	Battery Type	Sealed, Non-Spillable, Maintenance Free, Valve Regulated Lead Acid (VRLA)	
	Internal Battery Quantity (Default)	20	20
	Runtime: Full Load (minutes)	5 minutes	3 minutes
	Runtime: Half Load (minutes)	14 minutes	9 minutes
Surge Protection	Surge Energy Rating	880J	
	Surge Current Capability	1000A	
	Surge Response Time	8us	
	Surge Voltage Let-through	2KV	
Environmental	Audible Noise at 1m (3-ft.)	<55dB at 1 meter	<58dB at 1 meter
	Operating/(Storage) Temperature	0°C ~ +40°C / (-15°C ~ +60°C)	
	Relative Humidity	10 – 95% Non-condensing	
	Altitude	<1000m to Full Power (De-rate by 1% for every 100m above 1000m)	
Physical	Net Size - LxWxH (mm)	22.1" x 9.8" x 32.5" (561.1 x 250 x 826.5)	
	Shipping Size - LxWxH (mm)	28.5" x 14.6" x 37.0" (725 x 370 x 940)	
	Net Weight - (Kgs.)	237 lbs. (107.5)	274.5 lbs. (124.5)
	Shipping Weight (Kgs.)	272.3 lbs. (123.5)	309.8 lbs. (140.5)
Regulatory	Safety and Approvals	cTUVus, CE, RoHS2	
	EMC Verification	FCC Class A	
	Warranty	3 years parts and labor	

NOTE: The output capacity must be reduced to 90% when the output voltage is set to 208 VAC or 120 VAC.